



BOSCH



GLOBAL TOOLS CATALOG 2026 UAE

www.bosch-professional.com

POWER TOOLS

MEASURING TECHNOLOGY

PRO GARDEN

HIGH PREASURE WASHER



HEAVY DUTY TEAMMATES TO SIMPLIFY YOUR TOUGH JOBS.



For high-volume jobs in construction you need teammates you can count on even in the toughest of work challenges. Choose Bosch Professional cordless heavy duty tools, which, with their power and durability, and combined with the right accessories, will become indispensable members of your team.



DRILLING IN CONCRETE

Be it drilling holes in hardened concrete or breaking it, Bosch Professional rotary hammers with the right accessories excel at these kinds of applications.

CUTTING & GRINDING WITH SMALL ANGLE GRINDERS

If you are in an industry that requires multiple applications, our Bosch Professional small angle grinders are the right choice for you.



FIXING

Be it demanding applications requiring high torque and robustness or working with small diameters in hard-to-reach places, Bosch Professional provides a wide variety of the right tools and accessories for your construction work related applications.



DUST EXTRACTION

It is vital that you do everything you can to radically reduce the amount of dust in the air. The dust extraction solutions in the Bosch Professional range effectively prevent even fine dust invisible to the naked eye from becoming airborne. They can be connected to many compatible Bosch Professional tools and work directly where the dust is created.



IMPACT DRILL

GSB 600

Upgraded 13 mm impact drill for even more power



HEAVY DUTY



Order No.	06011A03LA
Technical Data	
Rated input power	600 W
No load speed	0 – 3,000 rpm
Impact rate at no load speed	0 – 48,000 bpm
Chuck capacity, min./max.	1.5 – 13 mm
Drilling capacity Steel, Wood, Stone	10mm, 25mm, 13mm
Weight	1.7 kg

GSB 600

Upgraded 13 mm impact drill for even more power



HEAVY DUTY



Order No.	06011A03LB
Technical Data	
Rated input power	600 W
No load speed	0 – 3,000 rpm
Impact rate at no load speed	0 – 48,000 bpm
Chuck capacity, min./max.	1.5 – 13 mm
Drilling capacity Steel, Wood, Stone	10mm, 25mm, 13mm
Weight	1.7 kg

GSB 13 RE

This impact drill has 750W of power, better relation power x weight and compact!



HEAVY DUTY



Order No.	0601217671
Technical Data	
Rated input power	600 W
No load speed	0 – 2,800 rpm
Impact rate at no load speed	0 – 44,800 bpm
Chuck capacity, min./max.	1.5 – 13 mm
Drilling capacity Steel, Wood, Stone	10mm, 25mm, 13mm
Weight	1.8 kg

GSB 16 RE PROFESSIONAL

A breakthrough that sets new standards, increased performance, better efficiency



HEAVY DUTY



Order No.	06012281K8
Technical Data	
Rated input power	750 W
No load speed	0 – 3,250 rpm
Impact rate at no load speed	0 – 48,500 bpm
Chuck capacity, min./max.	1.5 – 13 mm
Drilling capacity Steel, Wood, Stone	12mm, 25mm, 16mm
Weight	1.8 kg

GSB 24-2 IMPACT DRILL

2-gear impact drill for toughest applications with KickBack Control



HEAVY DUTY



Order No.	060119C801
Technical Data	
Rated input power	1,100 W
No load speed 1st gear	0 – 900 rpm
Impact rate at no load speed	0 – 15,300 / 51,000 bpm
Chuck capacity, min./max.	1.5 – 13 mm
Drilling capacity Steel, Wood, Stone	16/8mm, 40/25mm, 24/16mm
Weight	2.9 kg



ROTARY DRILL

GBM 6 RE DRILL PROFESSIONAL

1-gear rotary drill for precision drilling



HEAVY DUTY



Order No. 06014726P0

Technical Data

Rated input power	350 W
No-load speed, 1st gear	0 – 4,000 rpm
Rated torque	12.3 Nm
Chuck capacity, min./max.	1.5 - 10 mm
Drilling capacity Steel, Wood, Aluminium	6.5mm, 15mm, 8mm
Weight	1.2 kg

GBM 400 PROFESSIONAL

Powerful and compact for easy and flexible drilling



HEAVY DUTY



Order No. 06011C10L0

Technical Data

Rated input power	400 W
Power output	180 W
Drilling diameter in wood	20 mm
Drilling diameter in steel, aluminium	10 mm, 13mm
Chuck capacity, min./max.	10 mm
Weight	1.29 kg

GBM 1600 RE PROFESSIONAL

Power and Convenience for mixing & drilling applications



HEAVY DUTY



Order No. 06011B00L0

Technical Data

Rated input power	850 W
No-load speed, 1st gear	0 – 630 rpm
Rated torque	11.0 Nm
Chuck capacity, min./max.	3 – 16 mm
Strirrer Capacity, wood drilling, metal	160mm, 40mm, 16mm
Weight	3 kg

GBM 50-2 MAGNETIC CORE DRILL

Precise, efficient and convenient - the ideal solution for metal drilling



HEAVY DUTY



Order No. 06011B40L0

Technical Data

Rated input power	1,200 W
Bit holder	MT 2 - DIN 228
No load speed 1st/2nd gear	50-255/100-510 rpm
Rated torque	-
Drilling in Steel	50mm
Weight	14.7 kg



STIRRERS

GRW 140 MIXER PROFESSIONAL

Bosch's easy-to-use professional 2-gear mixer



HEAVY DUTY



Order No. 06011C40L0

Technical Data

Rated input power	1,400 W
Bit holder	M14
No load speed	480 / 750 rpm
Max. torque	10.0 / 7.0 Nm
Rated speed	-
Weight	4.2 kg

GRW 12 E PROFESSIONAL

Bosch's easy-to-use 1-gear stirrer



Order No. 06011A7070

Technical Data

Rated input power	1,200 W
Bit holder	Spindle
No load speed	1,000 rpm
Max. torque	12.0 Nm
Rated speed	- 620 rpm
Weight	5.3 kg

GRW 18-2 E MIXER

Bosch's powerful 2-gear stirrer



HEAVY DUTY



Order No. 06011A8000

Technical Data

Rated input power	1,600 W
Bit holder	Spindle
No load speed	450 / 1,050 rpm
Max. torque	45.0 / 19.0 Nm
Rated speed	- 250 / 580 rpm
Weight	4.2 kg

METAL CUT-OFF SAWS

GCO 230 PROFESSIONAL

Cuts steel faster and smoother



Order No. 0601B560P0

Technical Data	
Rated input power	2,300 W
Sound pressure level	104 dB(A)
Sound power level	113 dB(A)
No load speed	4,100 rpm
Tool dimensions (Width / Length / Height)	273 mm / 519 mm / 376 mm
Weight	13.5 kg

GCO 240 PROFESSIONAL

Redefining power in 14" cut-off saws



Order No. 0601B380P0

Technical Data	
Rated input power	2,400 W
Cutting disc diameter	355 mm
Cutting disc bore	25.4 mm
No load speed	3,800 rpm
Cutting capacity at rectangle 0°	100 x 196 mm
Weight	17 kg



MITRE SAWS

SLIDING MITRE SAW GCM 12 SDE

High cutting capacity and variable speed for various applications



Order No. 0601B23170

Technical Data	
Rated input power	1,800 W
Cutting disc diameter	305 mm
Cutting disc bore	30.0 mm
No load speed	3,100 – 4,000 rpm
Cutting capacity at rectangle 0°	70 x 400 mm
Weight	28.6 kg

SLIDING MITRE SAW GCM 12 GDL

Highest-precision sawing: mitre saw with Bosch's patented glide arm design



Order No. 0601B23600

Technical Data	
Rated input power	2,000 W
Cutting disc diameter	305 mm
Cutting disc bore	30.0 mm
No load speed	4,000 rpm
Cutting capacity at rectangle 0°	104 x 341 mm
Weight	29.4 kg

SLIDING MITRE SAW GCM 340-305 D

The heavy-duty, high-performance mitre saw with long-lasting accuracy



Order No. 0601B600L0

Technical Data	
Rated input power	1,800 W
Cutting disc diameter	305 mm
Cutting disc bore	25.4 mm
No load speed	4,050 rpm
Cutting capacity at rectangle 0°	105 x 340 mm
Weight	21.4 kg

COMPOUND MITRE SAW GCM 254

Make accurate cutting easier and more consistent with the tough professional mitre saw.



Order No. 0601B520L0

Technical Data	
Rated input power	1,750 W
Cutting disc diameter	254 mm
Cutting disc bore	25.4 mm
No load speed	5,000 – 5,000 rpm
Cutting capacity at rectangle 0°	90 x 130 mm
Weight	11.1 kg



BENCH GRINDERS

GBG 35-15 PROFESSIONAL

Heavy-duty, 350 W motor, double-wheeled bench grinder tackles the toughest jobs



Order No. 060127A300

Technical Data

Rated input power	350 W
No load speed	3,000 rpm
Grinding wheel, diameter	150 mm
Grinding wheel bore	20 mm
Grit	24 / 60
Weight	10.0 kg

GBG 60-20 PROFESSIONAL

Heavy-duty, 600 W motor, double-wheeled bench grinder tackles the toughest jobs



Order No. 060127A4L0

Technical Data

Rated input power	600 W
No load speed	3,000 rpm
Grinding wheel, diameter	200 mm
Grinding wheel bore	32 mm
Grit	24 / 60
Weight	15.0 kg



STRAIGHT GRINDER

GGG 30 LS PROFESSIONAL

Powerful, convenient, protective: the high-performance die grinder for versatile grinding tasks



Order No. 06012850P0

Technical Data

Rated input power	750 W
No load speed	7,000–33,000 rpm
Spindle collar diameter	43 mm
Max. grinding tool diameter	25 mm
Spanner size of grinding spindle	15 mm
Switch	Lockable Switch
Weight	1.7 kg

GGG 30 LPS PROFESSIONAL

The high-performance straight grinder with first-rate safety features



Order No. 06012852L0

Technical Data

Rated input power	750 W
No load speed	7,000–33,000 rpm
Spindle collar diameter	43 mm
Max. grinding tool diameter	25 mm
Spanner size of grinding spindle	15 mm
Switch	PROTECTION Switch
Weight	1.8 kg

GGG 5 LS PROFESSIONAL

The versatile grinder with precise speed control for better results



Order No. 06012242L0

Technical Data

Rated input power	550 W
No load speed	7,000–32,000 rpm
Spindle collar diameter	43 mm
Max. grinding tool diameter	25 mm
Spanner size of grinding spindle	15 mm
Switch	Lockable Switch
Weight	1.6 kg



SMALL ANGLE GRINDERS

GWS 700 PROFESSIONAL

Quality made Affordable



Order No. 06013A30L0

Technical Data

Rated input power	710 W
No load speed	12,000 – 12,000 rpm
Disc diameter	115 mm
Grinding spindle thread	M14
Switch	Lockable Switch
Weight	1.7 kg

GWS 750-100 PROFESSIONAL

900 W paddle switch, SAG delivers an incredible grip on safety and power.



Order No. 06013940L0

Technical Data

Rated input power	750 W
No load speed	11,000 rpm
Disc diameter	100 mm
Grinding spindle thread	M10
Switch	Lockable Switch
Weight	1.8 kg

GWS 750-115 PROFESSIONAL

New definition of power and handiness



Order No. 06013940L2

Technical Data

Rated input power	750 W
No load speed	11,000 rpm
Disc diameter	115 mm
Grinding spindle thread	M14
Switch	Lockable Switch
Weight	1.8 kg

GWS9-100 P

900 W paddle switch SAG delivers an incredible grip on safety and power



Order No. 06013965L0

Technical Data

Rated input power	900 W
No load speed	11,000 rpm
Disc diameter	100 mm
Grinding spindle thread	M10
Switch	PROTECTION SWITCH
Weight	1.9 kg

GWS 9-115 PROFESSIONAL

A 900 W built for tough jobs!



Order No. 06013960P3

Technical Data

Rated input power	900 W
No load speed	11,000 rpm
Disc diameter	115 mm
Grinding spindle thread	M14
Switch	Lockable Switch
Weight	1.9 kg

GWS 9-115 P PROFESSIONAL

900 W paddle switch SAG delivers an incredible grip on safety and power



Order No. 06013965P1

Technical Data

Rated input power	900 W
No load speed	11,000 rpm
Disc diameter	115 mm
Grinding spindle thread	M14
Switch	PROTECTION SWITCH
Weight	1.9 kg

GWS 12-125 PROFESSIONAL

Functional, ergonomic, and economical angle grinder for convenient everyday use



Order No. 06013A6170

Technical Data

Rated input power	1,200 W
No load speed	11,000 rpm
Disc diameter	125 mm
Grinding spindle thread	M14
Switch	Lockable Switch
Weight	2.2 kg

GWS 12-125 P PROFESSIONAL

Ergonomic angle grinder with PROtection switch and anti-vibration side handle for everyday use



Order No. 06013A62L0

Technical Data

Rated input power	1,200 W
No load speed	11,000 rpm
Disc diameter	125 mm
Grinding spindle thread	M14
Switch	Protection Switch
Weight	2.4 kg



SMALL ANGLE GRINDERS

GWS 1400 PROFESSIONAL

Tough grinding performance with versatility for regular use in the 1,400 W category.



Order No. 06018248P0

Technical Data

Rated input power	1,400 W
No load speed	11,000 rpm
Disc diameter	125 mm
Rubber backing pad, diameter	125 mm
Switch	Lockable Switch
Weight	2.2 kg

GWS 17-125 S PROFESSIONAL

New level of Power-to-grip-Size Ratio in the 1,700 W class plus Speed Selection



Order No. 06017D0300

Technical Data

Rated input power	1,700 W
No load speed	2,800 – 11,500 rpm
Disc diameter	125 mm
Grinding spindle thread	M14
Switch	Lockable Switch
Weight	2.2 kg

LARGE ANGLE GRINDERS

GWS 2000 (230 mm) PROFESSIONAL



Order No. 06018C10P3

Technical Data

Rated input power	2,000 W
No load speed	6,500 rpm
Disc diameter	230 mm
Grinding spindle thread	M14
Switch	Lockable Switch
Weight	5.4 kg

LARGE ANGLE GRINDERS

GWS 2200 (180 mm) PROFESSIONAL

HEAVY DUTY



Order No. 06018C00P0

Technical Data

Rated input power	2,200 W
No load speed	6,500 – 8,500 rpm
Disc diameter	180 mm
Grinding spindle thread	M14
Grinding head, diameter	140 mm
Switch	Lockable Switch
Weight	5.2 kg

GWS 2200 (230 mm) PROFESSIONAL

HEAVY DUTY



Order No. 06018C10P0

Technical Data

Rated input power	2,200 W
No load speed	6,500 rpm
Disc diameter	230 mm
Grinding spindle thread	M14
Grinding head, diameter	140 mm
Switch	PROTECTION SWITCH
Weight	5.4 kg

GWS 2200 P 230V PROFESSIONAL

HEAVY DUTY



Order No. 06018F4170

Technical Data

Rated input power	2,200 W
No load speed	6,500 rpm
Disc diameter	230 mm
Grinding spindle thread	M14
Grinding head, diameter	140 mm
Switch	PROTECTION SWITCH
Weight	5.3 kg

GWS 24-180 PROFESSIONAL

HEAVY DUTY



Order No. 06018C20P0

Technical Data

Rated input power	2,400 W
No load speed	8,500 rpm
Disc diameter	180 mm
Grinding spindle thread	M14
Grinding head, diameter	140 mm
Switch	Lockable Switch
Weight	5.7 kg

GWS 24-230 PROFESSIONAL

HEAVY DUTY



Order No. 06018C30P0

Technical Data

Rated input power	2,400 W
No load speed	6,500 rpm
Disc diameter	230 mm
Grinding spindle thread	M14
Grinding head, diameter	140 mm
Switch	Lockable Switch
Weight	5.8 kg



LARGE ANGLE GRINDERS

GWS 27-180 J PROFESSIONAL

HEAVY DUTY



Order No. 06018C4320

Technical Data

Rated input power	2,700 W
No load speed	8,500 rpm
Disc diameter	180 mm
Grinding spindle thread	M14
Grinding head, diameter	140 mm
Switch	Lockable Switch
Weight	5.7 kg

GWS 27-230 J PROFESSIONAL

HEAVY DUTY



Order No. 06018C30P0

Technical Data

Rated input power	2,700 W
No load speed	6,500 – 6,500 rpm
Disc diameter	230 mm
Grinding spindle thread	M14
Bore size, diameter	22,23 mm
Switch	Lockable Switch
Weight	6.0 kg



CONCRETE GRINDERS

GBR 15 CA PROFESSIONAL

Powerful dedicated concrete grinder with durable metal guard



Order No. 0601776070

Technical Data

Rated input power	1,500 W
No load speed	9,300 rpm
Grinding spindle thread	M14
Grinding head, diameter	125 mm
Main handle	Bow (rotating)
Weight	2.6 kg

AAC BLOCK CUTTERS

GAC 250 PROFESSIONAL

The hassle-free cutting experience you deserve



Order No. 06012B60L0

Technical Data

Rated input power	1,200 W
Cutter, length	250 mm
Chain pitch	3/8" (9.52 mm)
Chain speed	12 m/s
Chain gauge	1.3 mm
Weight	4.7 kg



DIAMOND TILE CUTTERS



GDC 140 PROFESSIONAL

Bosch range, same level as predecessor of current GDC 140.



Order No. 06013A40L0

Technical Data

Rated input power	1,400 W
No load speed	13,200 rpm
Cutting depth	35 mm
Disc diameter	115 mm
Max. cutting capacity (90°)	35 mm
Weight	2.9 kg

JIGSAWS

GST 680 PROFESSIONAL

Power up to excellent cutting



Order No. 06015B40L0

Technical Data

Rated input power	500 W
Saw, stroke length	20 mm
Stroke rate at no load	-
No load speed	-
Bevel angle	45 °
Weight	2.03 kg

GST 750 PROFESSIONAL

The reliable jigsaw for your daily use



Order No. 06015B41L0

Technical Data

Rated input power	520 W
Saw, stroke length	20 mm
Stroke rate at no load	800 – 3,100 rpm
Tool holder	T-Shank
Bevel angle	-45 – 45 °
Weight	2.37 kg

GST 8000 E PROFESSIONAL

Bosch professional jigsaw with the best cost-to-power ratio



Order No. 060158H0L0

Technical Data

Rated input power	710 W
Saw, stroke length	20 mm
Stroke rate at no load	800 – 3,100 spm
No load speed	3,100 rpm
Bevel angle	45 °
Weight	2.5 kg

GST 90 BE PROFESSIONAL

Reliable bow handle jigsaw for entry-level performance



Order No. 060158F070

Technical Data

Rated input power	650 W
Saw, stroke length	26 mm
Stroke rate at no load	500 – 3,100 spm
No load speed	3,100 rpm
Weight	2.6 kg

GST 150 BCE PROFESSIONAL

Robust bow handle jigsaw for tough applications



Order No. 0601513070

Technical Data

Rated input power	780 W
Saw, stroke length	26 mm
Stroke rate at no load	500 – 3,100 spm
Cable length	4 m
Weight	2.7 kg



CIRCULAR SAWS

GKS 9 PROFESSIONAL

The most powerful circular saw in its class!



Order No. 06015A2070

Technical Data

Rated input power	2,050 W
Saw blade diameter	235 mm
No load speed	5,300 rpm
Saw blade bore diameter	25 mm
Baseplate	383 x 170 mm
Weight	7.6 kg

GKS 140 PROFESSIONAL

High performance and resistance for rough cutting



Order No. 06016B30L1

Technical Data

Rated input power	1,400 W
No load speed	6,200 rpm
Saw blade diameter	184 mm
Saw blade bore diameter	20 mm
Baseplate	290 x 150 mm
Weight	3.7 kg



TABLE SAWS

GTS 254 PROFESSIONAL

Powerful and large cutting capacity table saw



Order No. 0601B450L0

Technical Data	
Rated input power	1,800 W
Saw blade diameter	254 mm
Incline setting	45° L / 0° R
Table size	555 x 555 mm
No load speed	4,300 rpm
Weight	24.4 kg

GTS 10 XC PROFESSIONAL

Versatile performance table saw



Order No. 0601B30470

Technical Data	
Rated input power	2,000 W
Saw blade diameter	254 mm
Incline setting	47° L / 1° R
Table size	640 x 705 mm
No load speed	4,200 rpm
Weight	35 kg

SAW STAND

GTA 60 W PROFESSIONAL

Table saw stand for ultimate mobility



Order No. 0601B12000

Technical Data	
Height of work bench	740 mm
Length of work bench	1,220 mm
Dimensions of table when folded up	1220 x 740 x 510 mm

PLANER

GHO 6500 PORTABLE PLANER

Powerful planer with up to 2.5 mm cutting depth!



Order No. 0601S960L0

Technical Data	
Rated input power	650 W
Planing width	82 mm
Rebating depth	0 – 9 mm
Tool height	140 mm
No load speed	16,500 rpm
Weight	2.8 kg

MULTI-CUTTER

GOP 30-28 MULTI-CUTTER

Best price-performance ratio in the Bosch Startlock-Plus category



Order No. 06012370L0

Technical Data	
Rated input power	300 W
Oscillation angle	1.4°
Tool width	46 mm
Tool height	75 mm
No load oscillation	8,000 – 20,000 opm
Weight	1.5 kg

DRILL SCREWDRIVER

GTB 650 PROFESSIONAL

Efficient, convenient and affordable Drywall Powerhouse within Reach



Order No. 06014A20P0

Technical Data	
Rated input power	650 W
Max. screw diameter	4.0 mm
Torque max.	12 Nm
Bit holder	1/4" Hex Uni
No load speed	0 – 5,000 rpm
Weight	1.4 kg



RANDOM ORBIT SANDERS

GEX 125 PROFESSIONAL

Comfortable sanding for getting more done



RANDOM ORBITAL SANDER 150MM STROKE 2.5MM

Handy sander for precision sanding work and for fine sanding – even on curves. Ideal for the automotive trade and paint shops.



RANDOM ORBITAL SANDER 150MM STROKE 5MM

Handy sander for precision sanding work and for fine sanding – even on curves. Ideal for the automotive trade and paint shops.



Order No.	06013A80L0
Technical Data	
Rated input power	280 W
No load speed	7,500–12,000 rpm
Sanding pad diameter	125 mm
Orbit diameter	2.6 mm
Orbital stroke rate	15,000–24,000 opm
Eccentricity	1.30 mm
Weight	1.4 kg

Order No.	0607350200
Technical Data	
Rated input power	170 W
No load speed	12000 rpm
Grinder tool diameter	150 mm
Hose inner diameter	10 mm
Toolholder / spindle thread	5/16"-24 UNF
Weight	0.7 kg

Order No.	0607350199
Technical Data	
Rated input power	170 W
No load speed	12000 rpm
Grinder tool diameter	150 mm
Hose inner diameter	10 mm
Toolholder / spindle thread	5/16"-24 UNF
Weight	0.7 kg

ORBITAL SANDER

GSS 140 A PROFESSIONAL

Comfortable sanding for efficient result



GSS 2300 PROFESSIONAL

Robust design for easy, fatigue-free sanding over many hours.



Order No.	06012A80L2
Technical Data	
Rated input power	220 W
No load speed	14,000–14,000 rpm
Sanding plate, length	112 mm
Orbit diameter	1.5 mm
Uncertainty K	3 dB
Weight	1.1 kg

Order No.	06012980L0
Technical Data	
Rated input power	190 W
No load speed	12,000 rpm
Sanding plate, length	182 mm
Orbit diameter	2.0 mm
Sanding plate, width	92 mm
Weight	1.5 kg



INDUSTRIAL ROUTER

GOF 130 PROFESSIONAL

No stops, no jams: the efficiency boost for your routing experience



GKF 550 PROFESSIONAL

The ultra-compact laminate trimmer, enabling effortless one-handed control



Order No.	06016B70P1
Technical Data	
Rated input power	1,300 W
No load speed	11,000–28,000 rpm
Router bit diameter	40 mm
Maximum router cage stroke	55 mm
Bit holder	6 – 8.0 mm
Weight	1.4 kg

Order No.	06016A00P0
Technical Data	
Rated input power	550 W
No load speed	33,000 rpm
Compatible collet diameters	6 mm
Tool dimensions (width)	90 mm
Tool dimensions (length)	90 mm
Weight	1.4 kg



ROTARY HAMMERS

GBH 220 PROFESSIONAL

So compact, so powerful – Bosch's rotary hammer now within reach



Order No. 06112A60L0

Technical Data

Rated input power	720 W
Impact rate at rated speed	0 – 4,800 bpm
Tool dimensions (length)	334 mm
Impact energy	2 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 22 mm / 30mm
Weight	2.3 kg

GBH 2-24 DRE PROFESSIONAL

Durable, reliable and superior – Drilling is now trouble-free with this tool.



Order No. 06112721L1

Technical Data

Rated input power	790 W
Impact rate at rated speed	0 – 4,200 bpm
Rated speed	0 – 930 rpm
Impact energy	2.7 J
Tool holder	SDS plus
Max. drilling diameter in metal / wood	13 mm / 30 mm
Weight	2.8 kg

GBH 2-24 DFR PROFESSIONAL

Durable, reliable and superior – Drilling is now trouble-free with this tool.



Order No. 06112730L1

Technical Data

Rated input power	790 W
Impact rate at rated speed	0 – 4,200 bpm
Rated speed	0 – 930 rpm
Impact energy	2.7 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 24 mm / 30mm
Weight	2.9 kg

GBH 2-26 DRE PROFESSIONAL

The fast all-rounder for daily use



Order No. 06112537P0

Technical Data

Rated input power	800 W
Impact rate at rated speed	0 – 4,000 bpm
Rated speed	0 – 900 rpm
Impact energy	2.7 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 16 mm / 30mm
Weight	2.9 kg

GBH 2-26 DFR PROFESSIONAL

The fast all-rounder for daily use



Order No. 06112547P0

Technical Data

Rated input power	800 W
Impact rate at rated speed	0 – 4,000 bpm
Rated speed	0 – 900 rpm
Impact energy	2.7 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 26 mm / 30mm
Weight	3 kg

GBH 2-28 F PROFESSIONAL

Strongest rotary hammer in Bosch 2 kg SDS plus category with quick-change chuck



Order No. 06112676P0

Technical Data

Rated input power	850 W
Impact rate at rated speed	0 – 4,000 bpm
Rated speed	0 – 900 rpm
Impact energy	3.2 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 28 mm / 30mm
Weight	3 kg

GBH 3-28 DFR PROFESSIONAL

Most versatile rotary hammer performance in the SDS plus category



Order No. 061124A070

Technical Data

Rated input power	850 W
Impact rate at rated speed	0 – 4,000 bpm
Rated speed	0 – 900 rpm
Impact energy	3.2 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 28 mm / 30mm
Weight	3.6 kg

GBH 4-32 DFR PROFESSIONAL

Robustness combined with durability and excellent performance in the SDS plus category



Order No. 0611332170

Technical Data

Rated input power	900 W
Impact rate at rated speed	0 – 3,600 bpm
Rated speed	0 – 800 rpm
Impact energy	4.2 J
Tool holder	SDS plus
Max. drilling diameter in metal / concrete / wood	13 mm / 32 mm / 32mm
Weight	4.7 kg



SDS-MAX ROTARY HAMMER

GBH 5-40 D PROFESSIONAL

Bosch's entry-level tool in the SDS max rotary hammer category



Order No. 0611269070

Technical Data

Rated input power	1,100 W
Impact rate at rated speed	1,500 – 2,900 bpm
Rated speed	170 – 340 rpm
Impact energy	8.5 J
Tool holder	SDS max
Drilling diameter in concrete with core cutters	40 – 90 mm
Weight	6.8 kg

GBH 5-40 DCE PROFESSIONAL

Bosch's SDS max rotary hammer for comfortable handling in extensive applications



Order No. 0611264070

Technical Data

Rated input power	1,150 W
Impact rate at rated speed	1,500 – 2,960 bpm
Rated speed	165 – 330 rpm
Impact energy	8.8 J
Tool holder	SDS max
Drilling diameter in concrete with core cutters	40 – 90 mm
Weight	6.8 kg



GBH 6-42 C PROFESSIONAL

Top-level protection for your heavy-duty drilling and chiselling needs



Order No. 06112780L0

Technical Data

Rated input power	1,300 W
Impact rate at rated speed	3,050 – 3,150 bpm
Rated speed	-
Impact energy	9 J
Tool holder	SDS max
Drilling diameter in concrete with core cutters	100 mm
Weight	7.7 kg

GBH 8-45 D PROFESSIONAL

The fast all-rounder for daily use



Order No. 0611265170

Technical Data

Rated input power	1,500 W
Impact rate at rated speed	1,475 – 2,700 bpm
Rated speed	165 – 300 rpm
Impact energy	12.5 J
Tool holder	SDS max
Drilling diameter in concrete with core cutters	125 mm
Weight	8.2 kg

GBH 12-52 D PROFESSIONAL

The fast all-rounder for daily use



Order No. 0611266170

Technical Data

Rated input power	1,700 W
Impact rate at rated speed	1,750 – 2,150 bpm
Rated speed	0 – 220 rpm
Impact energy	19 J
Tool holder	SDS max
Drilling diameter in concrete with core cutters	50 – 150 mm
Weight	11.5 kg



DEMOLITION HAMMERS

GSH500 MAX PROFESSIONAL

Bosch's SDS max demolition hammer for comfortable handling in extensive applications

HEAVY DUTY



Order No. 06113387L0

Technical Data

Rated input power	1,100 W
Impact rate at rated speed	2,900 bpm
Impact energy	7.8 J
Tool holder	SDS max
Weight	5.7 kg

GSH 5 CE PROFESSIONAL

Bosch's SDS max demolition hammer for comfortable handling in extensive applications

HEAVY DUTY



Order No. 0611321070

Technical Data

Rated input power	1,150 W
Impact rate at rated speed	1,300 – 2,900 bpm
Impact energy	8.3 J
Tool holder	SDS max
Weight	6.2 kg

GSH 7 VC PROFESSIONAL

Bosch's SDS max all-round performance demolition hammer with Vibration Control

HEAVY DUTY



Order No. 0611322070

Technical Data

Rated input power	1,500 W
Impact rate at rated speed	1,390 – 2,700 bpm
Impact energy	13 J
Tool holder	SDS max
Weight	8.3 kg

GSH 11 E PROFESSIONAL

Strongest Bosch SDS max demolition hammer for horizontal work

HEAVY DUTY



Order No. 0611316742

Technical Data

Rated input power	1,500 W
Impact rate at rated speed	1,050 – 1,890 bpm
Impact energy	16.8 J
Tool holder	SDS max
Weight	10.1 kg

GSH 11 VC PROFESSIONAL

Strongest Bosch SDS max demolition hammer with Vibration Control

HEAVY DUTY



Order No. 0611336070

Technical Data

Rated input power	1,700 W
Impact rate at rated speed	900 – 1,670 bpm
Impact energy	23 J
Tool holder	SDS max
Weight	11.4 kg

GSH 14 C PROFESSIONAL

Light, robust, powerful: the breaker hammer for versatile demolition tasks

HEAVY DUTY



Order No. 06113440L0

Technical Data

Rated input power	1,750 W
Impact rate at rated speed	1,900 – 1,950 bpm
Impact energy	28 J
Tool holder	HEX 22 mm
Weight	14.6 kg

BREAKERS

GSH 16-30 PROFESSIONAL

Universal performance breaker hammer with Vibration Control and 30-mm hexagon socket holder

HEAVY DUTY



Order No. 06113351P0

Technical Data

Rated input power	1,750 W
Impact rate at rated speed	1,300 – 1,300 bpm
Impact energy	41 J
Tool holder	HEX 30 mm
Weight	16.9 kg

GSH 27 VC PROFESSIONAL

Bosch's ultimate performance breaker with Vibration Control

HEAVY DUTY



Order No. 061130A0P0

Technical Data

Rated input power	1,900 W
Impact rate at rated speed	1,000 bpm
Impact energy	62 J
Tool holder	HEX 28 mm
Weight	29.5 kg



DIAMOND DRILLS

GDB 180 PROFESSIONAL

Versatile 2-gear diamond drill for hand-held and stand-mounted operations



Order No. 0601189800

Technical Data

Rated input power	2,000 W
No-load speed	900 / 2,800 rpm
Tool holder	1 1/4" UNC
Drilling range	180 mm
Drill spindle connecting thread	1 1/4" UNC
Weight	5.2 kg

GDB 350 WE PROFESSIONAL

High-powered 3-gear diamond drill for stand-mounted operation



Order No. 0601189900

Technical Data

Rated input power	3,200 W
Suitability	Wet drilling in concrete
Tool holder	1 1/4" UNC
Drilling range	350 mm
Drill spindle connecting thread	1 1/4" UNC
Weight	11.9 kg



DIAMOND DRILL STANDS

GCR 180 PROFESSIONAL

Suitable for GDB 180 WE diamond drill.



Order No. 0601190100

Technical Data

Column length	767 mm
Drill stroke	514 mm
Working length, Z axis	455 mm
Drilling diameter	180 mm
Securing, type	bolted
Weight	9.5 kg

GCR 350 PROFESSIONAL

Suitable for GDB 350 WE diamond drill.



Order No. 0601190200

Technical Data

Column length	955 mm
Drill stroke	580 mm
Drilling diameter	350 mm
Working length, Z axis	550 mm
Securing, type	bolted
Weight	12.6 kg

DIAMOND WATER CONTAINER

Water Pressure Container is suitable for wet diamond drilling work on construction sites that do not have a water connection



Order No. 2609390308

Technical Data

Packaging type	Non-packaged product, no Euro hole
Water Tank Capacity	10L



METAL SURFACE FINISHING

UNIVERSAL ANGLE POLISHER GPO 14 CE

Convenient handling, fast work progress, and best results



Order No. 0601389073

Technical Data

Rated input power	1,400 W
Cup wheel, diameter	180 mm
Surface brush, diameter	175 mm
Grinding spindle thread	M14
No load speed	750 – 3,000 rpm
Weight	2.5 kg

UNIVERSAL ANGLE POLISHER GPO 11-180 S

Powerful, ergonomic, and low-vibration polisher designed for your comfort



Order No. 06013A23L0

Technical Data

Rated input power	1,100 W
Polishing sponge, diameter	180 mm
Main handle	Rattail
Grinding spindle thread	M14
No load speed	3,800 rpm
Weight	2.1 kg

BLOWERS

GBL 650 PROFESSIONAL

Compact yet powerful for cleaning efficiency



Order No. 06019M40L0

Technical Data

Rated input power	650 W
Sound power level	95 dB(A)
Sound pressure level	103 dB(A)
Uncertainty K	3 dB
Dimension (width/length/height)	181/436/197 mm
Weight	1.7 kg

GBL 800 E PROFESSIONAL

The handy tool for blowing and dust extraction



Order No. 06019804P0

Technical Data

Rated input power	820 W
No load speed	16,000 rpm
Volumetric flow rate	4.5 m ³ /min
Tool dimension (width)	94 mm
Tool dimension (length)	500 mm
Weight	2.25 kg

HEAT GUNS

GHG 180 PROFESSIONAL

Keep up the heat without missing a beat!



Order No. 060194D0L0

Technical Data

Rated input power	1,800 W
Working temperature	60 – 550 °C
Airflow	350 – 550 L/min
Heat up time	1 s
Uncertainty K	3 dB
Weight	0.75 kg

GHG 20-63 PROFESSIONAL

High-performance heat gun with temperature control



Order No. 06012A62L0

Technical Data

Rated input power	2,000 W
Working temperature	50 – 630 °C
Airflow	150 – 500 L/min
Control, airflow	3
Uncertainty K	3 dB
Weight	0.65 kg

FOAM CUTTER

GSG 300 FOAM RUBBER CUTTER

Specialist foam cutter for curved and straight cuts in soft materials



Order No. 0601575142

Technical Data

Rated input power	350 W
Stroke rate at no load	3,500 spm
Cutting depth	300 mm
Voltage, electrical	240 V
Uncertainty K	3 dB
Weight	1.6 kg



RECIPROCATING SAWS

GSA 120 PROFESSIONAL

Cut more with the latest transmission, ultra durable reciprocating saw



Order No. 06016B10L0

Technical Data

Rated input power	1,200 W
No load speed	0 - 3,000 spm
Cable length	3 m
Cutting depth in wood	220 mm
Saw, stroke length	29 mm
Weight	3.7 kg

GSA 12-30 PROFESSIONAL

An ergonomic saw, much faster now for your demolition work



Order No. 06016C70L0

Technical Data

Rated input power	1,250 W
Cut thickness, wood	220 mm
Cut thickness, steel	20 mm
Uncertainty K	5 dB
Stroke length	30 mm
Weight	3.7 kg



WET/DRY EXTRACTORS

GAS 12-25 PL PROFESSIONAL

Powerful L-class dust extractor for wet or dry applications



Order No. 060197C1L0

Technical Data

Rated input power	1,250 W
Filter surface area	2,300 cm ²
Container volume, net	21 l
Dust bag volume, net	20 l
Airflow rate (turbine)	65 l/s
Weight	4.7 kg

GAS 35 L SFC+ PROFESSIONAL

L-Class dust extractor for wet/dry applications with semi-automatic filter cleaning



Order No. 06019C3060

Technical Data

Rated input power	1,200 W
Filter surface area	6,150 cm ²
Container volume, net	23 l
Container volume, net, water	19.2 l
Airflow rate (turbine)	74 l/s
Weight	11.6 kg

INDUSTRIAL VACUUM CLEANER GAS 400 A

Non-stop work with full productivity



Order No. 06019M00L0

Technical Data

Rated input power	1,200 W
Filter surface area	3,600 cm ²
Container volume, net	28 l
Dust class	L
Airflow rate (turbine)	72 l/s
Weight	14 kg

WALL CHASERS

GNF 35 CA PROFESSIONAL

Bosch's wall chaser for all-round use



Order No. 0601621703

Technical Data

Rated input power	1,400 W
No load speed	9,300 rpm
Adjustable groove depth	0 - 35 mm
Cutting width	3 mm - 3.9 cm
Disc diameter	150 mm
Weight	4.7 kg

GNF 65 A PROFESSIONAL

Heavy-duty wall chaser



Order No. 0601368703

Technical Data

Rated input power	2,400 W
No load speed	5,200 rpm
Adjustable groove depth	20 - 65 mm
Cutting width	3 mm - 4 cm
Disc diameter	230 mm
Weight	8.4 kg

DRYWALL SANDER

GTR 550 PROFESSIONAL

Bosch's new drywall sander for effortless sanding in all directions



Order No. 06017D40L0

Technical Data

Rated input power	550 W
No load speed	340 - 910 rpm
Sanding pad diameter	215 mm
Sanding sheet diameter	225 mm
Backing pad hardness	Soft
Weight	4.8 kg

CORDLESS SCREWDRIVER

BOSCH GO (GEN 3) PROFESSIONAL

NEW

Practical and convenient – the versatile screwdriver for delicate applications



Order No. 06019H2201

Technical Data

Rated input power	3.6 V
No-load speed	360 rpm
Max. screw diameter	5 mm
Rated Torque	2.5 / 5 Nm
Bit Holder	1/4" Internal Hexagonal
Weight	0.31 kg

Comes with C-Pin charger



12V CORDLESS RANGE

GSR 120-LI DRILL DRIVER PROFESSIONAL

High-powered 2-in-1 for less



Order No. 06019G80L0

Technical Data

Battery Voltage	12 V
No-load speed	0 – 400 / 0 – 1,500 rpm
Torque (soft/hard/max.)	14/30/- Nm
Torque settings	20+1
Chuck capacity, min./max.	0.8 / 10 mm
Weight excl. battery	0.8 kg

Comes with 2x2Ah Battery+Charger

GSB 120-LI IMPACT DRILL DRIVER

Highly flexible, highly economical



Order No. 06019G81L0

Technical Data

Battery Voltage	12 V
No-load speed	0 – 400 / 0 – 1,500 rpm
Torque (soft/hard/max.)	14/30/- Nm
Torque settings	20+2
Max. impact rate	22,500 bpm
Weight excl. battery	0.9 kg

Comes with 2x2Ah Battery+Charger

GSR 12V-15 FC DRILL DRIVER

Redefine your limits – the flexibility of five solutions in one compact tool



Order No. 06019F60L0

Technical Data

Battery voltage	12.0 V
No-load speed	0 – 400 / 0 – 1,300 rpm
Torque (soft/hard/max.)	15/30/- Nm
Torque settings	20+1
Chuck capacity, min./max.	1 / 10 mm
Weight excl. battery	0.6 kg

Comes with 2x2Ah Battery+Charger

GWS 12V-76 ANGLE GRINDER

World's first angle grinder in the 12 V category



Order No. 06019F2000

Technical Data

Battery voltage	12 V
Disc diameter	76 mm
No-load speed	19,500 rpm
Grinding spindle thread	M5
Bore size, diameter	10 mm
Weight	0.90 kg

Batteries & Charger not included

CORDLESS ANGLE DRILL GWB 12V-10

Compact angle drill in the 12 V category for hard-to-reach places



Order No. 0601390905

Technical Data

Battery voltage	12 V
Max. screw diameter	up to 6 mm
Max. drilling diameter in wood	10 mm
Max. torque	3/11/- Nm
Drilling in wood max dia	10 mm
Weight	1.20 kg

Batteries & Charger not included

CORDL RECIPROCATING SAW GSA 12V-14

Bosch's most compact 12V-reciprocating saw



Order No. 060164L902

Technical Data

Battery voltage	12 V
Cutting depth in wood	65 mm
Stroke lengths	14.5 mm
Cutting depth in metal	50 mm
Tool dimensions (width)	60 mm
Weight	1.20 kg

Batteries & Charger not included

12V CORDLESS RANGE

GKF 12V-8 ROUTER

World's first 12 V professional edge router with a unique design for perfect control



Order No. 06016B0002

Technical Data

Battery voltage	12 V
No load speed	13,000 rpm
Sound pressure level	71 dB(A)
Uncertainty K	3 dB
Tool dimensions (width)	80 mm
Weight	1.1 kg

Batteries & Charger not included

GKS 12V-26 CIRCULAR SAW

Compact and handy design: The 12 V cordless circular saw for cuts up to 26.5 mm



Order No. 06016A1001

Technical Data

Battery voltage	12 V
No load speed	1,400 rpm
Saw blade diameter	85 mm
Max. cutting capacity in wood (90°)	26.5 mm
Saw blade bore diameter	15 mm
Weight	1.40 kg

Batteries & Charger not included



GHO 12V-20 BRUSHLESS PLANER

First professional 12 V planer for a new level of tool control



Order No. 06015A7000

Technical Data

Battery voltage	12 V
No load speed	14,500 rpm
Planing depth	0 - 2 mm
Rebating depth	0 - 17 mm
Planing width, max.	56 mm
Weight	1.5 kg

Batteries & Charger not included

GST 12V-70 JIGSAW

Compact barrel grip jigsaw in the 12 V category



Order No. 06015A1001

Technical Data

Battery voltage	12 V
No load speed	1,500 - 2,800 spm
Bevel angle	0 - 45 °
Cutting depth in wood	70 mm
Cutting depth in aluminium	5 mm
Weight	1.5 kg

Batteries & Charger not included

12V STARTER KIT PROFESSIONAL

2-gear impact drill for toughest applications with KickBack Control



Order No. 1600A019R9

Technical Data

Battery voltage	12 V
Cell type	Li-Ion
Battery charging voltage	10.8 - 12 V
Charge current	4.0 A
Battery 1 capacity	2.0 Ah
Weight	0.45 kg

Comes with 2x2Ah Battery+Charger

GAL 12 V-40 CHARGER PROFESSIONAL

The 12 V fast charger



Order No. 1600A019R4

Technical Data

Battery voltage	12 V
Cell type	Li-Ion
Battery charging voltage	10.8 - 12 V
Charge current	4.0 A
Charg. time at bat. cap. 2.0Ah	24/35 min
Weight	0.45 kg

Comes with 1 Charger

GBA 12 V 2.0AH LI-ION BATTERY

Compact 2.0 Ah battery in the 12 V category



Order No. 1600Z0002X

Technical Data

Battery voltage	12 V
Cell type	Li-Ion
Battery dimensions (width x length x height)	47 x 50 x 85 mm
Weight	0.175 kg

Comes with 1 battery

GBA 12 V 4.0AH LI-ION BATTERY

The compact 12 volt batteries with 4.0 Ah



Order No. 1600Z0002Y

Technical Data

Battery voltage	12 V
Cell type	Li-Ion
Battery dimensions (width x length x height)	80 x 160 x 95 mm
Weight	0.37 kg

Comes with 1 battery

CORDLESS DRILL/DRIVERS

GSR 185-LI PROFESSIONAL

More work with no limits



Order No. 06019K3003

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	21/50/- Nm
No load speed (1st gear / 2nd gear)	0 - 500 / 0 - 1,900 rpm
Chuck capacity, min./max.	1.5 / 13 mm
Torque settings	20+1
Weight incl. battery	1.3 kg

Batteries & Charger not included

GSR 185-LI PROFESSIONAL

Powerful cordless drill driver with compact head length and perfect tool control



Order No. 06019K30L0

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	21/50/- Nm
No load speed (1st gear / 2nd gear)	0 - 500 / 0 - 1,900 rpm
Chuck capacity, min./max.	1.5 / 13 mm
Torque settings	20+1
Weight excl. battery	0.93 kg

Comes with 2x2Ah Battery+Charger

GSR 18V-50 SOLO PROFESSIONAL

Tough brushless motor for heavy-duty jobs



Order No. 06019H5002

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	28/50/50 Nm
No load speed (1st gear / 2nd gear)	0 - 460 / 0 - 1,800 rpm
Chuck capacity, min./max.	1.5 / 13 mm
Torque settings	20+1
Weight excl. battery	1.0 kg

Batteries & Charger not included

GSR 18V-150 C PROFESSIONAL

When strength counts – the clever drill driver for unrivalled power and control



KICKBACK CONTROL



Order No. 06019J5001

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	84/100/150 Nm
No load speed (1st gear / 2nd gear)	0 - 550 / 0 - 2,200 rpm
Chuck capacity, min./max.	1.5 / 13 mm
Torque settings	25+1
Weight excl. battery	2.1 kg



CORDLESS IMPACT DRILL DRIVERS

GSB 183-LI PROFESSIONAL

Make tough jobs easier – with the versatile 18V cordless impact drill driver



Order No. 06019K91L0

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	21/56/56 Nm
No load speed (1st gear / 2nd gear)	0 – 440 / 0 – 1,650 rpm
Torque settings	20
Weight excl. battery	1.2 kg

Comes with 2x2Ah Battery+Charger

GSB 185-LI PROFESSIONAL

More work with no limits



Order No. 06019K31L0

Technical Data

Battery voltage	18 V
Max. impact rate	27,000 bpm
Torque (soft/hard/max.)	21/50/- Nm
No load speed (1st gear / 2nd gear)	0–500/0–1,900 rpm
Torque settings	20+2
Weight excl. battery	0.99 kg

Comes with 2x2Ah Battery+Charger

GSB 185-LI PROFESSIONAL

More work with no limits



Order No. 06019K3103

Technical Data

Battery voltage	18 V
Max. impact rate	27,000 bpm
Torque (soft/hard/max.)	21/50/- Nm
No load speed (1st gear / 2nd gear)	0–500/0–1,900 rpm
Torque settings	20+2
Weight excl. battery	0.99 kg

Batteries & Charger not included

GSB 18V-50 PROFESSIONAL

Robust brushless motor for durability and flexibility



Order No. 06019H51L0

Technical Data

Battery voltage	18 V
Max. impact rate	27,000 bpm
Torque (soft/hard/max.)	28/50/- Nm
No load speed (1st gear / 2nd gear)	0 – 2,500 / 0 rpm
Torque settings	20+2
Weight excl. battery	1.1 kg

Comes with 2x2Ah Battery+Charger

GSB 18V-65 PROFESSIONAL

The compact, robust impact drill for tough screwdriving applications

KICKBACK CONTROL



Order No. 06019N3102

Technical Data

Battery voltage	18 V
Max. impact rate	27,000 bpm
Torque (soft/hard/max.)	31/65/76 Nm
No load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,100 rpm
Torque settings	20
Weight excl. battery	1.12 kg

Batteries & Charger not included

GSB 18V-65 PROFESSIONAL

The compact, robust impact drill for tough screwdriving applications

KICKBACK CONTROL



Order No. 06019N31L0

Technical Data

Battery voltage	18 V
Max. impact rate	27,000 bpm
Torque (soft/hard/max.)	31/65/76 Nm
No load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,100 rpm
Torque settings	20
Weight excl. battery	1.12 kg

Comes with 2x2Ah Battery+Charger

GSB 18V-90 C PROFESSIONAL

Powerful cordless impact drill with compact head length and perfect tool control

KICKBACK CONTROL



Order No. 06019K6100

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	35/64/- Nm
No load speed (1st gear / 2nd gear)	0 – 630 / 0 – 2,100 rpm
Chuck capacity, min./max.	1.5 / 13 mm
Torque settings	21
Weight excl. battery	1.1 kg

Batteries & Charger not included

GSB 18V-150 C PROFESSIONAL

When strength counts – the clever impact drill driver for unrivalled power and control

KICKBACK CONTROL



Order No. 06019J5101

Technical Data

Battery voltage	18 V
Torque (soft/hard/max.)	84/100/150 Nm
No load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Max. impact rate	30,000 bpm
Torque settings	25+2
Weight excl. battery	2.2 kg

Batteries & Charger not included



CORDLESS IMPACT DRIVER/WRENCH

GDR 18V-215 PROFESSIONAL

Your Go-To tool for fast and accurate screw driving



Order No. 06019N2020

Technical Data

Battery voltage	18 V
Impact rate (1st level)	0-3,000 bpm
No load speed (1st level)	0-2,100 rpm
No load speed (2nd level)	0-3,300 rpm
Screw Diameter Bolt Size	M6-16
Torque, max.	215 Nm
Weight excl. battery	1.0 kg

Batteries & Charger not included

GDX 18V-285 PROFESSIONAL

The ideal tool for bolting and screw driving with one tool holder.



Order No. 06019N21L2

Technical Data

Battery voltage	18 V
Impact rate (1st level)	0-3,000 bpm
No load speed (1st level)	0-2,000 rpm
No load speed (2nd level)	0-2,800 rpm
Screw Diameter Bolt Size	M8-18
Torque, max.	285 Nm
Weight excl. battery	1.1 kg

Comes with 2x2Ah Battery+Charger

GDX 18 V-200 C PROFESSIONAL

Bosch's most powerful 18 V impact driver with 2-in-1 bit holder - with brushless motor



Order No. 06019G4204

Technical Data

Battery voltage	18 V
Impact rate	0-4,000 bpm
No load speed (1st level)	0-1,100 rpm
No load speed (2nd level)	0-2,300 rpm
Screw Diameter Bolt Size	M6-16
Torque, max.	200 Nm
Weight excl. battery	1.2 kg

Batteries & Charger not included

CONVENIENTLY SAVING TIME

Single tool for both screwdriving and bolting.



COMFORTABLE & ERGONOMIC

Comfortable to use for long periods thanks to ergonomic handle.



POWERFUL TOOL

Bolting tool with 285 Nm torque performs wrenching applications with ease 2-speed selection for multiple type of applications.



GDX 18V-200 C PROFESSIONAL

Bosch's most powerful 18 V impact driver with 2-in-1 bit holder - with brushless motor



Order No. 06019G42L0

Technical Data

Battery voltage	18 V
Impact rate	0-4,000 bpm
No load speed (1st level)	0-1,100 rpm
No load speed (2nd level)	0-2,300 rpm
Screw Diameter Bolt Size	M6-16
Torque, max.	200 Nm
Weight excl. battery	1.2 kg

Comes with 2x4Ah Battery+Charger

GDS 18V-350 PROFESSIONAL

Small size. Big impact. The cordless impact wrench for PRO bolting



Order No. 06019M50L1

Technical Data

Battery voltage	18 V
Impact rate	0-3,400 bpm
No load speed (1st level)	0-1,200 rpm
No load speed (2nd level)	0-1,700 rpm
Bolt Size	M10-18
Torque, max.	350 Nm
Weight excl. battery	1.1 kg

Comes with 2x4Ah Battery+Charger

GDS 18V-400 PROFESSIONAL

Bosch's Powerful Mid Torque Impact Wrench - Durable and Robust



Order No. 06019K00L0

Technical Data

Battery voltage	18 V
Impact rate	3,700 bpm
No load speed (1st level)	0-2,500 rpm
No load speed (2nd level)	0 rpm
Bolt Size	M10-20
Torque, max.	400 Nm
Weight excl. battery	1.25 kg

Comes with 2x5Ah Battery+Charger

CORDLESS IMPACT WRENCH

GDS 18V-780 PROFESSIONAL

Compact and powerful: the easy way to tackle tough work



Order No. 06019P40L1

Technical Data

Battery voltage	18 V
Impact rate	1,900-2,400 bpm
Impact rate (2nd level)	2,100 bpm
Impact rate (3rd level)	2,400 bpm
Torque, max.	780 Nm
BITURBO	No
Weight excl. battery	2.1 kg

Comes with 2x5Ah Battery+Charger



GDS 18V-1000 PROFESSIONAL

Full power, no cord: 1/2" high torque impact wrench with BITURBO Brushless technology



Order No. 06019J8300

Technical Data

Battery voltage	18 V
Impact rate	0-2,600 bpm
No load speed (1st level)	0-800 rpm
No load speed (2nd level)	0-1,200 rpm
Bolt Size	M14-24
Torque, max.	1,000 Nm
Weight excl. battery	2.9 kg

Batteries & Charger not included

GDS 18V-1050 H PROFESSIONAL

Full power at its best: 3/4" high torque impact wrench with BITURBO Brushless technology



Order No. 06019J8500

Technical Data

Battery voltage	18 V
Impact rate	0-2,600 bpm
No load speed (1st level)	0-800 rpm
No load speed (2nd level)	0-1,200 rpm
Bolt Size	M14-24
Torque, max.	1,050 Nm
Weight excl. battery	2.9 kg

Batteries & Charger not included

GDS 18V-1600 HC PROFESSIONAL

Exceptional cordless power: 3/4" high-torque impact wrench with BITURBO Brushless technology



Order No. 06019M1000

Technical Data

Battery voltage	18 V
Impact rate	0-2,350 bpm
No load speed (1st level)	0-800 rpm
No load speed (2nd level)	0-1,300 rpm
No load speed (3rd level)	0-1,750 rpm
Torque, max.	1,600 Nm
Weight excl. battery	3.2 kg

Batteries & Charger not included

STRIRrer

MIXER GRW 18V-120 PROFESSIONAL

The compact alternative to a conventional mixer



Order No. 06011C2080

Technical Data

Battery voltage	18 V
Bit holder	M14
Stirrer basket diameter max	120 mm
Sound pressure level	74 dB(A)
Uncertainty K	3 dB
Sound power level	82 dB(A)
Weight	2.9 kg

Batteries & Charger not included



RECIPROCATING SAWS

GSA 185-LI PROFESSIONAL

Speedy demolition work with more freedom and less fatigue



Order No. 06016C0020

Technical Data

Battery voltage	18 V
Cutting depth in wood	230 mm
Stroke lengths	28 mm
Cutting depth in metal profiles and metal pipes	150 mm
Weight excl. battery	3.2 kg

Batteries & Charger not included

METAL SHEARS

GSC 18V-16 E PROFESSIONAL

Ergonomic cordless shear with brushless motor technology for powerful metal cutting



Order No. 0601926300

Technical Data

Battery voltage	18 V
No load stroke rate	230 mm
Battery capacity	12.0 Ah
Cutting capacity in steel (400 N/mm ²), max.	1.6 mm
Weight excl. battery	1.6 kg

Batteries & Charger not included



CIRCULAR SAWS

GKM 18V-50 PROFESSIONAL

Precise and easy metal sawing: faster work progress, limited sparks and chips



Order No. 06016B8000

Technical Data

Battery voltage	18 V
Saw blade diameter	136 mm
No load speed	4,250 rpm
Saw blade bore diameter	20 mm
Weight excl. battery	2.2 kg

Batteries & Charger not included

GKS 185-LI PROFESSIONAL

Cordless and compact all-rounder for robust sawing – with saw blade on the right



Order No. 06016C1221

Technical Data

Battery voltage	18 V
Saw blade diameter	165 mm
No load speed	5,000 rpm
Saw blade bore diameter	20 mm
Weight excl. battery	2.8 kg

Batteries & Charger not included

GKS 18V-68 GC PROFESSIONAL

Cordless flexibility with corded power – outstanding performance and handling



Order No. 06016B5100

Technical Data

Battery voltage	18 V
Saw blade diameter	190 mm
No load speed	2,500 – 5,000 rpm
Guide rail compatible	Yes
Weight excl. battery	4.3 kg

Batteries & Charger not included



18V HEAT GUN

GHG 18V-50 PROFESSIONAL

Flexible 18V heat gun for working on the go



Order No. 06012A6500

Technical Data

Battery voltage	18 V
Working temperature	300 - 500 °C
Airflow	175 L/min
Heat up time to 300°C	6 s
Temperature levels	2
Weight excl. battery	0.59 kg

Batteries & Charger not included

18V BLOWER

GBL 18V-120 PROFESSIONAL

Blower for quick cleanup in the 18 V category



Order No. 06019F5100

Technical Data

Battery voltage	18 V
No load speed	17,000 rpm
Airflow	120 m³/h
Max. air speed	270 km/h
Tool dimensions (length)	523 mm
Weight excl. battery	1.1 kg

Batteries & Charger not included



18V JOBSITE LIGHTS

GLI 18V-1900 PROFESSIONAL

The versatile floodlight with 1,900 lumens in the 18 V category



Order No. 0601446400

Technical Data

Battery voltage	18 V
Luminous flux	1,900 lm
Max. operating time 18 V	100 mins/Ah
Max. operating time 14.4 V	80 mins/Ah
Number of brightness levels	2
Weight excl. battery	1.6 kg

Batteries & Charger not included

GLI 18V-800 PROFESSIONAL

Bright light where you need it: versatile work light with 800 lumens



Order No. 0601443600

Technical Data

Battery voltage	18 V
Luminous flux	800 lm
Max. operating time 18 V	-
Number of brightness levels	3
Battery voltage, works with	18 V
Weight excl. battery	0.5 kg

Batteries & Charger not included

GLI 18V-300 PROFESSIONAL

The long-lasting stick light with 300 lumens in the 18 V category



Order No. 06014A1100

Technical Data

Battery voltage	18 V
Luminous flux	300 lm
Max. operating time 14.4 V	250 mins/Ah
Max. operating time 18 V	300 mins/Ah
Battery voltage, works with	18.0 V
Weight excl. battery	0.3 kg

Batteries & Charger not included



CORDLESS JIGSAWS

GST 183-LI PROFESSIONAL

Easier to move, faster to cut



Order No. 06015B7020

Technical Data

Battery voltage	18 V
Tool holder	T-Shank
Stroke rate at no load	0 – 3,300 spm
Stroke height	20 mm
Bevel angle	-45 – 45 °
Weight excl. battery	1.6 kg

Batteries & Charger not included



GST 185-LI BARREL PROFESSIONAL

Cordless freedom without limits - with barrel grip



Order No. 06015B2021

Technical Data

Battery voltage	18 V
Tool holder	T-Shank
Stroke rate at no load	0 – 3,500 spm
Stroke height	26 mm
Bevel angle	-45 – 45 °
Weight excl. battery	2 kg

Batteries & Charger not included

GST 185-LI PROFESSIONAL

Reliable cordless problem solver for all applications - with bow grip



Order No. 06015B3021

Technical Data

Battery voltage	18 V
Tool holder	T-Shank
Stroke rate at no load	0 – 3,500 spm
Stroke height	26 mm
Bevel angle	-45 – 45 °
Weight excl. battery	2 kg

Batteries & Charger not included



CORDLESS CONCRETE NAILERS

GNB 18V-38 PROFESSIONAL

Easy and efficient fastening in concrete with powerful BITURBO Brushless technology



Order No. 06019L7071

Technical Data

Battery voltage	18 V
Nail diameter	2.7 – 3 mm
Nail length	13 – 38 mm
Nail/Staple type	Pin
Magazine capacity	22 Pcs
Weight excl. battery	4.1 kg

Comes with 2x4Ah Battery+Charger

COMPATIBLE NAILS

For GNB 18V-38

NB-16
16mm for Concrete - Smooth

1600A02F4K

NB-19
19mm for Concrete - Smooth

1600A02F4L

NB-25
25mm for Concrete - Smooth

1600A02F4M

NB-32
32mm for Concrete - Smooth

1600A02F4N

NB-38
38mm for Concrete - Smooth

1600A02F4P

NK-35
35mm for Concrete - Knurled

1600A02F4R

NM-13
13mm for Steel - Graduated

1600A02F4S

NM-16
16mm for Steel - Graduated

1600A02F4T

NM-19
19mm for Steel - Graduated

1600A02F4U

CORDLESS DRYWALL SCREWDRIVER

GTB 185-LI PROFESSIONAL

Reliable cordless problem solver for all applications - with bow grip



Order No. 06019K7021

Technical Data

Battery voltage	18 V
Torque, max. (hard/soft)	32 Nm
No load speed	0 - 4,500 rpm
Bit holder	1/4" Hex Uni
Torque, max. (soft)	5.2 Nm
Weight excl. battery	0.95 kg

Batteries & Charger not included



CORDLESS RIVET GUNS



GRG 18V-16 C PROFESSIONAL

Versatile riveting with no limits



Order No. 06019K5000

Technical Data

Battery voltage	18 V
Pull force, max.	16,000 N
Weight excl. battery	1.6 kg

Comes with 4 nose pieces
(3.0/3.2 mm, 4.0 mm, 4.8/5.0 mm, 6.4 mm)

Batteries & Charger not included

ROUTER

GLF 18V-8 PROFESSIONAL

Affordable 18V laminate trimmer. The budget-friendly solution for edge profiling and laminate trimming specialists



Order No. 06016C6020

Technical Data

Battery voltage	18 V
No load speed	10,000 - 30,000 rpm
Collet diameters	6 mm / 1/4" / 8 mm
Sound pressure level	81 dB(A)
Sound power level	89 dB(A)
Weight excl. battery	1.1 kg

Batteries & Charger not included

CORDLESS DUST EXTRACTORS

GAS 18V-1 PROFESSIONAL

Compact handheld 18 V dry vacuum cleaner makes short work of rough dirt



Order No. 06019C6200

Technical Data

Battery voltage	18 V
Container volume	0.7 l
Max. vacuum pressure (turbine)	60 mbar
Max. airflow rate (turbine)	10 l/s
Operating time 18 V	7 mins/Ah
Weight excl. battery	1.3 kg

Batteries & Charger not included

GAS 18V-10L PROFESSIONAL

L-Class 18V mobile dust extractor for wet/dry applications



Order No. 06019C6302

Technical Data

Battery voltage	18 V
Container volume, gross	10L
Max. vacuum pressure (turbine)	115 mbar
Max. airflow rate (turbine)	34,0 l/s
Operating time 18 V	4 mins/Ah
Weight excl. battery	4.7 kg

Batteries & Charger not included

CORDLESS SDS-PLUS ROTARY HAMMERS

GBH 185-LI PROFESSIONAL

Next-level work with efficiency, safety and control



Order No. 0611924020

Technical Data

Battery voltage	18 V
Impact rate at rated speed	0 – 4,675 bpm
Tool holder	SDS plus
Rated speed	0 – 1,050 rpm
Impact energy nominal	1.9 J
Weight excl. battery	2.3 kg

Batteries & Charger not included

GBH 185-LI PROFESSIONAL

Next-level work with efficiency, safety and control



Order No. 06119240L1

Technical Data

Battery voltage	18 V
Impact rate at rated speed	0 – 4,675 bpm
Tool holder	SDS plus
Rated speed	0 – 1,050 rpm
Impact energy nominal	1.9 J
Weight excl. battery	2.3 kg

Comes with 2x4Ah Battery+Charger

GBH 18V-18 X ONE CHUCK PROFESSIONAL

Compact 18V ONECHUCK rotary hammer with Kick-Back Control



Order No. 06119271L0

Technical Data

Battery voltage	18 V
Tool holder	SDS plus Cylindrical, Hex
Max. drilling diameter in metal	10 mm
Max. drilling diameter in wood	18 mm
Impact energy nominal	1.5 J
Weight excl. battery	1.8 kg

Comes with 2x2Ah Battery+Charger

GBH 187-LI ONE CHUCK PROFESSIONAL

Live the freedom that your work demands

ONE CHUCK



Order No. 0611923120

Technical Data

Battery voltage	18 V
Impact rate at rated speed	0-4,350 bpm
Tool holder	SDS plus, Cylindrical, HEX
Drilling dia. in concrete with hammer drill bits	4-24mm
Max. drilling diameter in metal/Wood	13mm/30mm
Weight excl. battery	3 kg

Batteries & Charger not included

GBH 187-LI ONE CHUCK PROFESSIONAL

Live the freedom that your work demands



Order No. 06119231L0

Technical Data

Battery voltage	18 V
Impact rate at rated speed	4,350 bpm
Tool holder	SDS plus
Drilling dia. in concrete with hammer drill bits	4-24mm
Max. drilling diameter in metal/Wood	13mm/30mm
Weight excl. battery	2.9 kg

Comes with 2x4Ah Battery+Charger

GBH 187-LI PROFESSIONAL

Live the freedom that your work demands



Order No. 06119230L0

Technical Data

Battery voltage	18 V
Impact rate at rated speed	0-4,350 bpm
Tool holder	SDS plus
Drilling dia. in concrete with hammer drill bits	4-24mm
Max. drilling diameter in metal/Wood	13mm/30mm
Weight excl. battery	2.9 kg

Comes with 2x5Ah Battery+Charger

GBH 187-LI PROFESSIONAL

Efficient rotary hammer for everyday work with built-in Bluetooth Connectivity



Order No. 0611923020

Technical Data

Battery voltage	18 V
Impact rate at rated speed	4,350 bpm
Tool holder	SDS plus
Drilling dia. in concrete with hammer drill bits	4-24mm
Max. drilling diameter in metal/Wood	13mm/30mm
Weight excl. battery	2.9 kg

Batteries & Charger not included



CORDLESS SDS-PLUS ROTARY HAMMERS

GBH P 18V-26 F (C) PROFESSIONAL

Universal rotary hammer with quick-change chuck in the SDS plus cordless category



Order No. 0611910000

Technical Data

Battery voltage	18 V
Tool holder	SDS plus
Hammer drilling diameter range in concrete	4-26mm
Impact energy nominal	2.6 J
Weight excl. battery	3 kg

Batteries & Charger not included

GBH 18V-34 CF PROFESSIONAL

The market's most powerful cordless SDS plus hammer



Order No. 0611914021

Technical Data

Battery voltage	18 V
Tool holder	SDS plus
Hammer drilling diameter range in concrete	8-32 mm
Impact energy nominal	5.8 J
Weight excl. battery	5 kg

Batteries & Charger not included

SDS-MAX ROTARY

GBH 18V-36 C PROFESSIONAL

Outstanding compactness and power



Order No. 0611915021

Technical Data

Battery voltage	18 V
Tool holder	SDS Max
Hammer drilling diameter range in concrete	14-35mm
Impact energy nominal	7.0 J
Weight excl. battery	5.3 kg

Batteries & Charger not included

SDS-MAX DEMOLITION

GBH 18V-45 C PROFESSIONAL

Cordless freedom with corded performance - the heavy-duty all-rounder for concrete drilling and chiselling up to 45 mm.



Order No. 0611913120

Technical Data

Battery voltage	18 V
Tool holder	SDS Max
Hammer drilling diameter range in concrete	14-35mm
Impact energy nominal	12.5 J
Weight excl. battery	9.3 kg

Batteries & Charger not included

GSH 18V-5 PROFESSIONAL

Cordless freedom with corded performance: SDS max demolition hammer



Order No. 0611918200

Technical Data

Battery voltage	18 V
Tool holder	SDS Max
Optimal tool control with Softstart, Impact energy	6.5 J
Adaptive Speed control (ASC) and lock on button for continuous chiselling	
Weight excl. battery	5.3 kg

Batteries & Charger not included



CORDLESS ANGLE GRINDERS

GWS 18V-8 (115 mm) PROFESSIONAL

Compact and swift,
exceptional for everyday
cutting tasks



Order No. 06019N9004

Technical Data

Battery voltage	18 V
No load speed	11,000 rpm
Disc diameter	115 mm
Grinding spindle thread	M14
Weight excl. battery	1.6 kg

Batteries & Charger not included

GWS 18V-8 (125 mm) PROFESSIONAL

Compact and swift,
exceptional for everyday
cutting tasks



Order No. 06019N9000

Technical Data

Battery voltage	18 V
No load speed	11,000 rpm
Disc diameter	125 mm
Grinding spindle thread	M14
Weight excl. battery	1.6 kg

Batteries & Charger not included

GWS 18V-10 P (125MM) PROFESSIONAL

Improved power level
and tool control in the
18 V category



Order No. 06019J4100

Technical Data

Battery voltage	18 V
No load speed	9,000 rpm
Disc diameter	125 mm
Grinding spindle thread	M14
Weight excl. battery	1.9 kg

Batteries & Charger not included

GWS 18V-11 PROFESSIONAL

All-round performer for
maximum cutting and
grinding versatility.



Order No. 06019N4101

Technical Data

Battery voltage	18 V
No load speed	9,000 rpm
Disc diameter	115 mm
Grinding spindle thread	M14
Weight excl. battery	1.7 kg

Batteries & Charger not included

GWS 18V-180 P PROFESSIONAL

Cutting depth like a
large angle grinder
with the size and
weight of a small one



Order No. 06019H6L01

Technical Data

Battery voltage	18 V
No load speed	6,100 rpm
Disc diameter	180 mm
Grinding spindle thread	M14
Weight excl. battery	2.8 kg

Batteries & Charger not included

GGG 18V-20 STRAIGHT GRINDER PROFESSIONAL

A compact and
powerful cordless
straight grinder with a
long lifetime



Order No. 06019B5401

Technical Data

Battery voltage	18 V
No load speed	24,000 rpm
Tool holder	Collet
Tool dimensions (length)	310 mm
Weight excl. battery	1.2 kg

Batteries & Charger not included



BATTERIES

ProCORE18V 4.0 Ah

Performance of a conventional battery in the most compact size and weight.



Order No. 1600A016GB

Technical Data

Battery voltage	18 V
Weight	0.515 kg
Battery capacity	4 Ah

ProCORE18V 5.5 Ah

High performance battery for up to 1,800 Watt corded power.



Order No. 1600A02149

Technical Data

Battery voltage	18 V
Weight	0.955 kg
Battery capacity	5.5 Ah

ProCORE18V 8.0 Ah

High performance battery for up to 1,800 Watt corded power.



Order No. 1600A016GK

Technical Data

Battery voltage	18 V
Weight	0.955 kg
Battery capacity	8 Ah

ProCORE18V 12.0 Ah

Maximum performance battery with 12 Ah capacity for longest runtime.



Order No. 1600A016GU

Technical Data

Battery voltage	18 V
Weight	1.35 kg
Battery capacity	12 Ah

CHARGERS

GAL 18V-40

The compact 18 V charger.



Order No. 1600A019RK

Technical Data

Battery charging voltage	14.4 – 18 V
Weight	0.55 kg
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	24/35 min

GAL 1880 CV

The compact 18 V charger.



Order No. 1600A019RK

Technical Data

Battery charging voltage	14.4 – 18 V
Weight	0.7 kg
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	10/25 min

GAL 18V-160

The world's fastest 18 V charger.



Order No. 1600A02T5H

Technical Data

Battery charging voltage	14.4 – 18 V
Weight	0.95 kg
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	15/25 min

GAL 18V6-80

Continuous charging for non-stop work – multi-bay charger with 6 battery interfaces.



Order No. 1600A01U9M

Technical Data

Battery charging voltage	14.4 – 18 V
Weight	1.8 kg
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	16/24 min

STARTER SETS

2x GBA 18V 4.0Ah + GAL 18V-40

2x 18 V battery with 4.0 Ah capacity for extended runtime and fast charger.



Order No. 1600A019S1

Technical Data

Battery voltage	18 V
Battery 1 weight	0.619 kg
Battery charging voltage	14.4 – 18 V
Charger weight	0.55 kg
Charg. time at bat. cap. 4.0 Ah (80%/100%) approx.	48/65 min

ONE BATTERY FITS ALL! USE ONE BATTERY AND CHARGER ON EVERY TOOL WITHIN THE SAME VOLTAGE!



CHARGERS BATTERIES

12V



GBA 12V 2.0Ah GBA 12V 3.0Ah GBA 12V 4.0Ah



GAL 12V-40

18V



GBA 18V 1.5Ah GBA 18V 2.0Ah GBA 18V 3.0Ah GBA 18V 4.0Ah W
GBA 18V 5.0Ah ProCore 18V 4.0Ah ProCore 18V 8.0Ah ProCore 18V 12Ah



GAL 18V-160 C GAX 18V-30 GAL 18V-40 GAL 1880 CV

MADE TO GO BEYOND

One cordless tool is never enough.
Create your own, flexible PRO-MIX set!

PRO-MIX

CHOOSE THE 18V BATTERY FOR THE MOST EFFICIENT POWER OUTPUT!

Interchangeable battery system since 2008

Bosch Professional



PRO

EXPERT

GBA 18V
2Ah



GBA 18V
4Ah



GBA 18V
5Ah



EXBA 18V
4Ah



EXBA 18V
5.5Ah



EXBA 18V
8Ah



EXBA 18V
15Ah



ROUTERS

Router Laminate/Palm (GLF/GKF)

Router Mid-Full Size (GDF)

Drywall Router (GCU)

ANGLE GRINDERS & METALWORKING

Small Angle Grinder (GWS/GWX)

Large Angle Grinder (GWS/GWX)

Angle Grinder & Metalworking (GGS/GSC/GRG/GNA)

Concrete Grinder (GBR)

BLOWERS

Compact blower (GBL)

Leafblower (GBL)

GARDEN TOOLS

Brushcutter (GFR)
Grass Trimmer (GRT)

Brushcutter Bike Handle (GFR BH)

Lawnmower (GRA)

Hedge Cutter & Pole Hedge Cutter (GHE TP/FP)

Chainsaw (GKE < 25 cm)

Chainsaw (GKE ≥ 25 cm)
Pole Chainsaw (GKE TP)

Pruner (GGP)

MEASURING TOOLS

Line Laser (GLL)

Rotation Laser (GRL)

STIRRERS

Stirrer (GRW)

HEAT GUNS

Heat Gun (GHG)

POLISHERS

Polisher (GPO/GPX)

CONCRETE VIBRATORS

Concrete Vibrator (GVC)

BISCUIT JOINERS

Biscuit Joiner (GFF)

WALL CHASERS

Wall Chaser (GNF)

CAULK GUNS

Caulk Gun (GCG)

GREASE GUNS

Grease Gun (GFP)

A CORDLESS SYSTEM THAT DOES ITS JOB. SO YOU CAN DO YOURS.

The Professional 18V System combines highest performance with compact dimensions and minimum weight to make your toughest jobs easier. Benefit from the ultimate in performance, uncompromising compatibility and maximum freedom on your job site.

+87%¹ MORE POWER

ProCORE18V: latest cell technology and intelligent battery management.



Up to +135%² LONGER LIFETIME

COOLPACK 2.0 technology: prevents the battery from overheating.

Up to +151%³ EXTENDED RUNTIME

Excellent battery performance: When other batteries switch off, you just keep working.



**PERFECTLY
ENGINEERED FOR HIGHEST
PERFORMANCE.**

9 min to 50%⁴ FASTEST CHARGING

Get back to work faster than ever thanks to the world charging champion GAL 18V-160 C Professional.



¹ GAL 18V 8.0Ah vs. ProCORE 18V 8.0Ah: 800W vs. 1620W. ² vs. no Bosch COOLPACK 2.0 technology. ³ ProCORE 18V 8.0Ah vs. GBA 18V 6.0Ah Application: Drilling a hole 25 mm in diameter using the SDS-Plus C30V/37 concrete. ⁴ As of May 2019: It takes 9 minutes to charge the ProCORE 18V 4.0Ah to 50% with GAL 18V-160 C (in Power Boost mode).

THE PROOF IS OUT – ACHIEVE MORE WITH THE ProCORE18V.



+30%⁵

**REMOVES MORE
MATERIAL IN 2 MIN**

+70%⁶

MORE HOLES



+151%⁷

MORE HOLES

ProCORE18V – OUR MOST POWERFUL BATTERIES EVER.

ProCORE18V 4.0Ah

All the power of a standard battery – not its weight.

ProCORE18V 8.0Ah

The perfect balance between weight and power – with up to 1600W corded power.

ProCORE18V 12.0Ah

Maximum performance and runtime.

⁵ ProCORE18V 8.0Ah vs. GBA 18V 6.0Ah. Application: Two-minute metal edge grinding with GW5 18V-125 50°, ceramic grit wheel (2 601 601 502).

⁶ ProCORE18V 8.0Ah vs. GBA 18V 6.0Ah. Application: Drilling holes in a 10x10 cm piece of softwood using a 32 mm spade bit.

⁷ ProCORE18V 8.0Ah vs GBA 18V 6.0Ah. Application: Drilling a hole 25 mm in diameter using the SDS-plus C30/37 concrete.



ONE BATTERY FITS ALL

All our 18V batteries and chargers are compatible with all new and existing tools in the Professional 18V System since 2008.



AMPShare ALLIANCE

Our 18V batteries and chargers are part of the fast-growing AMPShare battery alliance. With just one battery, you can power many tools from many brands beyond Bosch Professional.

COMBINE AS YOU LIKE

Mixing and matching has never been easier. There's a tool for every trade, and all our 18V tools, batteries, and chargers are compatible.



Powered by



PROFESSIONAL

18V
SYSTEM

ONE SYSTEM. UNLIMITED POTENTIAL.

The Professional 18V System makes hard work easier with uncompromising compatibility, up to 2,000 W of power, and a global battery alliance that takes you even beyond Bosch.



LEADING BATTERY TECH

Longer runtimes and lifetimes meet the world's fastest charging technology*. Our 18V batteries are designed to take on the toughest applications.

CORDED PERFORMANCE

Need corded power? The 18V system includes our high-performance BITURBO Brushless tool series, which can unleash up to 2,000 W of equivalent corded power with just one ProCORE18V (≥ 5.5 Ah) battery.

*GAL 18V-160 C Professional: 9 minutes to reach 50% charge of the ProCORE18V 4.0Ah (in Power Boost Mode). As of 2022.



BOSCH

Invented for life

Explore for yourself:

Start successful projects with a precise measurement.

It's in your hands. Bosch Professional.

Digital measuring tools by Bosch Professional.

www.bosch-professional.com

Every little detail should be spot on from the start of a construction project. Digital measuring tools by Bosch Professional enable you to guarantee your client absolute precision – whether you are measuring distances, angles and inclines, aligning objects or detecting cables and mould risk areas. Together you're the perfect team.

Your advantages at a glance.

efficient ✓

Optimal tools that save time, deliver the highest precision and prevent errors.

reliable ✓

High-quality technology for exceptionally precise results even in adverse lighting conditions, dusty environments or rough terrain.

connected ✓

Bluetooth®-capable measuring tools enable measuring data to be sent quickly and easily to a smartphone or tablet directly on location.



LASER MEASURES

GLM 25-23 PROFESSIONAL

Easy-to-use, pocket-sized laser measure for professionals.



Order No. 0601072W00

Technical Data

Measuring range, up to	25 m
Laser colour	Red
DOT MATRIX DISPLY	
Weight, approx.	0.9kg
Measurement accuracy, typical	± 2.0 mm
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Power supply	2 x 1.5 V LR03 (AAA)

GLM 40 PROFESSIONAL

All in one – all relevant measurement modes in one compact design.



Order No. 0601072902

Technical Data

Measuring range, up to	40 m
Laser colour	Red
Dust and splash protection	IP 54
Memory capacity (values)	10
Measurement accuracy, typical	± 1.5 mm
Units of measurement	m/cm, ft/inch
Power supply	2 x 1.5 V LR03 (AAA)

GLM 50-22 PROFESSIONAL

Laser measuring for rough job sites and easily adjustable to individual needs.



Order No. 0601072500

Technical Data

Measuring range, up to	50 m
Laser colour	Red
Dust and splash protection	IP 65
Memory capacity (values)	10
Measurement accuracy, typical	± 1.5 mm
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Power supply	2 x 1.5 V LR6 (AA)

GLM 50-27 C PROFESSIONAL

Fast, reliable, and outstandingly robust: laser measuring for rough jobsites.



Order No. 0601072T00

Technical Data

Measuring range, up to	50 m
Laser colour	Red
Dust and splash protection	IP 65
Memory capacity (values)	30
Measurement range of incline measurement	0 – 360° (4 x 90°)
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Power supply	2 x 1.5 V LR6 (AA)

GLM 50-27 CG PROFESSIONAL

Robust & reliable laser measure with green laser for excellent visibility.



Order No. 0601072U00

Technical Data

Measuring range, up to	50 m
Laser colour	Green
Dust and splash protection	IP 65
Memory capacity (values)	30
Measurement range of incline measurement	0 – 360° (4 x 90°)
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Power supply	2 x 1.5 V LR6 (AA)

GLM 100-25 C PROFESSIONAL

Precise laser measure for easy indoor and outdoor measuring and documenting.



Order No. 0601072Y00

Technical Data

Measuring range, up to	100 m
Laser colour	Red
Dust and splash protection	IP 54
Memory capacity (values)	50
Digital viewfinder	Integrated
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Power supply	3 x 1.5 V LR6 (AA)

GLM 150-27 C PROFESSIONAL

Advanced laser measure for long distances even outdoors with smart documentation.



Order No. 0601072Z00

Technical Data

Measuring range, up to	150 m
Laser colour	Red
Dust and splash protection	IP 54
Memory capacity (values)	50
Digital viewfinder	Integrated
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Power supply	1 x 3.6 V Li-Ion battery (3120 mAh)



LINE LASER

GLL 2 PROFESSIONAL

Upgraded 18 mm impact drill for even more power



Order No. 0601063A01

Technical Data

Projection	2 Lines
Working range, value	10 m
Colour of laser line	Red
Accuracy	± 0.05 mm/m
Self levelling range	± 4°
Power supply	2 x 1.5 V LR6 (AA)
Weight, approx.	0.28 kg

GLL 3 X PROFESSIONAL

Upgraded 18 mm impact drill for even more power



Order No. 0601063CJ0

Technical Data

Projection	Compact 3 line laser
Working range, value	15 m
Colour of laser line	Red
Accuracy	± 0.5 mm/m
Laser diode	650 nm, < 1 mW
Power supply	4 x 1.5 V LR6 (AA)
Weight, approx.	0.5 kg

GLL 2-10 PROFESSIONAL

Compact and intuitive line laser for short-distance applications



Order No. 0601063L00

Technical Data

Projection	2 Lines
Working range	10 m
Colour of laser line	red
Accuracy	± 0.3 mm/m
Self levelling range	± 4°
Power supply	3 x 1.5 V LR6 (AA)
Dust and splash protection	IP 54

GLL 2-15 G+LB10+BT150 PROFESSIONAL



Order No. 0601063W01

Technical Data

Projection	2 Lines
Working range, value	15 m
Colour of laser line	Green
Accuracy	± 0.3 mm/m
Laser diode	650 nm, < 1 mW
Dust and splash protection	IP 64
Power supply	4 x 1.5 V LR6 (AA)

GLL 12-22 G PROFESSIONAL

Durable, green beam line laser for reliable levelling



Order No. 0601065320

Technical Data

Projection	2 lines
Working range, value	12 m
Colour of laser line	Green
Accuracy	± 0.6 mm/m
Laser diode	500-540 nm, < 5 Mw
Dust and splash protection	IP 55
Power supply	2 x 1.5 V LR6 (AA)

GLL 2-20 G + LB 10 & CEILING CLIP PROFESSIONAL

Line laser with 360° horizontal green line



Order No. 0601065000

Technical Data

Projection	2 Lines
Working range, value	10 m
Colour of laser line	Green
Accuracy*	± 0.4 mm/m
Self levelling range	± 4°
Dust and splash protection	IP 64
Power supply	4 x 1.5 V LR6 (AA)



LINE LASER

GLL 20-22 G PROFESSIONAL

Upgraded 13 mm Impact drill for even more power



Order No.	0601065601
Technical Data	
Projection	2 Lines
Working range, value	10 m
Colour of laser line	Green
Accuracy	± 0.4 mm/m
Laser diode	500-40 nm, < 10 mW
Dust and splash protection	IP 64
Power supply	4 x 1.5 V LR6 (AA)

GLL 3-80 PROFESSIONAL

3 x 360° for visibility on a new level



Order No.	0601063S00
Technical Data	
Projection	3 x 360° Line
Working range, value	30 m
Working range with receiver	120 m
Colour of laser line	Red
Accuracy	± 0.3 mm/m
Dust and splash protection	IP 54
Compatible laser receivers	LR 6 + 7
Power supply	4 x 1.5 V LR6 (AA)

GLL 3-80 C + BT 150 (CARTON KIT)

Visibility on a new level in 3 x 360°. Simply Connected.



Order No.	0601063R01
Technical Data	
Projection	3 x 360° Line
Working range, value	30 m
Working range with receiver	120 m
Colour of laser line	Red
Accuracy	± 0.2 mm/m
Dust and splash protection	IP 54
Compatible laser receivers	LR 6 + 7
Power supply	4 x 1.5 V LR6 (AA)

GLL 80-33 G PROFESSIONAL

Upgraded 13 mm Impact drill for even more power



Order No.	0601065500
Technical Data	
Projection	3 x 360° Line
Working range, value	30 m
Working range with receiver	80 m (radius)
Colour of laser line	Green
Accuracy	± 0.3 mm/m
Dust and splash protection	IP 65
Compatible laser receivers	LR 7
Power supply	4 x 1.5 V LR6 (AA)

GLL 12V-100-33 CG PROFESSIONAL

Robust and intuitive 12V line laser for effortless alignment



Order No.	0601065470
Technical Data	
Projection	3 x 360° Line
Working range, value	30 m
Working range with receiver	100 m (radius)
Colour of laser line	Green
Accuracy	± 0.3 mm/m
Dust and splash protection	IP 65
Compatible laser receivers	LR 7
Comes with 12V 2Ah Li-ion Battery + Charger + L-Boxx	



BUILDING TRIPOD

GCL2-15 PROFESSIONAL

Compact and versatile for short-distance levelling applications



Order No.	0601066E00
Technical Data	
Projection	2 Lines / 2 points
Working range, value	15 m
Accuracy	± 0.3 mm/m
Colour of laser line	Red
Range Laser points, max.	10 m (top)/(bottom)
Dust and splash protection	IP 54
Plumb point accuracy	± 0.7 mm/m
Power supply	3 x 1.5 V LR6 (AA)

GCL 2-15+RM1+CARRY CASE PROFESSIONAL

Compact and versatile for short-distance levelling applications



Order No.	0601066E02
Technical Data	
Projection	2 Lines / 2 points
Working range, value	15 m
Accuracy	± 0.3 mm/m
Colour of laser line	Red
Range Laser points, max.	10 m (top)/(bottom)
Dust and splash protection	IP 54
Plumb point accuracy	± 0.7 mm/m
Power supply	3 x 1.5 V LR6 (AA)

GCL 12V-50-22 CG PROFESSIONAL

Robust 12V combi laser for reliable alignment



Order No.	0601066S70
Technical Data	
Projection	2 Lines / 2 points
Working range, value	25 m
Working range with receiver	50 m
Colour of laser line	Green
Range Laser points, max.	10 m (top)
Dust and splash protection	IP 65
Compatible laser receivers	LR 7
Comes with 12V 2Ah Li-ion Battery + Charger + L-Boxx	

ANGLE MEASURER

GAM 220 MF PROFESSIONAL

Fast calculation of mitre angles



Order No.	0601076600
Technical Data	
Power supply	4 x 1.5 V LR6 (AA)
Measurement range	0° - 220°
Accuracy	± 0.1°
Arm length	40 cm
Weight, approx.	1.20 kg

INSPECTION CAMERA

GIC 120C PROFESSIONAL

Efficient inspection and documentation of hard-to-reach areas



Order No.	0601241200
Technical Data	
Power supply	4x1.5 V LR6 battery (AA)
Display size	3,5"
Display resolution	320 x 240 Pixel
Length of camera cable	120 cm
Weight, approx.	0.64 kg

OPTICAL LEVELS

GOL 32 D OPTICAL LEVEL

Robust and reliable - ideal for outdoor use



Order No.	0601068500
Technical Data	
Unit of measure	360 degrees
Magnification	32 x
Accuracy	± 1 mm at 30 m
Working range, value	120 m
Working range	120 m
Dust and splash protection	IP 54

Use with BT 170 Tripod and GR 500 Measuring Rod

BUILDING TRIPOD

BT 150 PROFESSIONAL

Absolutely secure stance on any floor



Order No.	0601096800
Technical Data	
Work height, up to	157 cm
Work height	55 - 157 cm
Weight, approx.	1.3 kg
Tripod thread	1/4"
Weight, approx.	5,500 kg

BT 170 HD PROFESSIONAL

Robust aluminium construction with high stability on any floor



Order No.	0601091800
Technical Data	
Work height, up to	165 cm
Work height	107 - 165 cm
Weight, approx.	5,500 kg
Tripod thread	5/8"
Weight, approx.	5,500 kg

MEASURING ROD

GR 500 PROFESSIONAL

For all measurements of floor heights



Order No.	0601094600
Technical Data	
Length	5.0 m
Sections	5
Units of measurement	m/cm
Material	Aluminium
Length of camera cable	120 cm

UNIVERSAL MOUNT

BM3 PROFESSIONAL

The easy solution for GLL 2-15 Professional



Order No.	0601015000
Technical Data	
Arm length	40 cm
Suitable for	GLL 2-10, GCL 2-15, GCL 2-15 G, GCL 2-50
Tool dimensions (length)	155 mm
Tool dimensions (height)	173 mm
Weight, approx.	0,300 kg

LASER RECEIVER

LR 7 PROFESSIONAL



Order No.	0601069100
Technical Data	
Power supply	2 x 1.5 V LR6 (AA)
Dust and splash protection	IP 54
Type of receiver	Combi- and line lasers
Measuring accuracy (fine/rough)	± 1 mm/± 3 mm
Weight, approx.	0.150 kg





BOSCH

NEW ARRIVAL



ELECTRICAL TESTERS

ELECTRICAL TESTER

CLAMP METER GMC 600-15

Efficient and robust True RMS Clamp meter with inverted LCD display for precise readings



Order No. 0601077600

Technical Data	
Voltage AC/DC	600 V
Current AC	600 A
Measuring category	CAT IV 300 V CAT III 600 V
Protection class	IP54
Drop test resistance	2 m
Power source	2x1.5 V LR06 (AA) / BA 3.7V 1.0Ah A Professional

DIGITAL MULTIMETER GDM 600-15

Efficient multimeter with inverted display and True RMS precision



Order No. 0601077300

Technical Data	
Voltage AC/DC	600 V
Current AC	10 A AC/DC
Measuring category	CAT III 600 V
Protection class	IP65
Drop test resistance	2 m
Power source	2x1.5 V LR06 (AA) / BA 3.7V 1.0Ah A Professional

FORK METER GFM 1000-15

Reliable and robust True RMS Fork meter with inverted LCD screen for quick AC current checks



Order No. 0601077400

Technical Data	
Voltage AC/DC	1000 V
Current AC	200 A
Measuring category	CAT IV 600 V CAT III 1000 V
Protection class	IP54
Drop test resistance	2 m
Power source	2x1.5 V LR06 (AA) / BA 3.7V 1.0Ah A Professional

VOLTAGE TESTER GVD 1000-17

Robust Non-Contact Voltage Tester for Enhanced Safety



Order No. 0601077000

Technical Data	
Voltage AC/DC	90-1000 V AC / 24-1000 V AC
Current AC	-
Measuring category	CAT IV 1000 V
Protection class	IP67
Drop test resistance	2 m
Power source	2x1.5 V LR03 (AAA)

VOLTAGE TESTER GVT 1000-15

Robust voltage tester for enhanced safety and efficiency



Order No. 0601077800

Technical Data	
Voltage AC/DC	12-1000 V
Current AC	-
Measuring category	CAT IV 600 V / CAT III 1000 V
Protection class	IP65
Drop test resistance	1 m
Power source	2x1.5 V LR03 (AAA)

ACCESSORIES

MAGNET HOLDER 1 PROFESSIONAL

Magnetic holder for hands-free efficiency



Order No. 1600A038CY

Technical Data	
Cable Break Detection	no

MEASURING PROBE MS 90

Flexible measuring strips for precise electrical work



Order No. 1600A038D2

Technical Data	
AC current	10 A
Safety class	CAT IV 600 V / CAT III 1000 V
Safety class with removed caps	CAT II 1000 V
Measuring strips cable length	90 cm
Cable Break Detection	no



PROFESSIONAL

18V
SYSTEM

READY FOR OUTDOORS: PROFESSIONAL 18V SYSTEM

Your job. Your turf. It's time to grow your Professional 18V System – with our new suite of high-performance and high comfort outdoor tools.

Bosch Professional



For more information:
www.bosch-professional.com/ae/en/

CORDLESS LAWNMOWER GRA 18V2-46

Product Number
06008C8000

Included in this model:
• Mulch plug
• 2x isolator key



TECHNICAL DATA

Brushless Motor
Cutting width: 46 cm
Height-of-cut range: 30 – 70 mm
Collection box capacity:
60 l Noise level 94 dB(A)

RECOMMENDED ACCESSORIES

 Accessory Set
Lawnmower Blade 46cm
F016800638

CORDLESS LEAF BLOWER GBL 18V-750

Product Number
06008D2000

Included in this model:
• Nozzle



RECOMMENDED ACCESSORIES

 Nozzle - Pro Blowing Extension
Adapter
F016800657

 Nozzle Concentrator - Pro
Round Blowing Adapter
F016800658

TECHNICAL DATA

Brushless Motor
Max. air speed: 198 km/h
Max. airflow: 780 m³/h



BOSCH

PROFESSIONAL CORDLESS CHAINSAW GKE 18V-40

Product Number
06008D3000


Included in this model:
• Chain cover
• Sorenh



TECHNICAL DATA

Brushless Motor
Chain pitch: .325" (8.25 mm)
Chain speed: 12.4 m/s
Chain gauge: 1.1 mm
Noise level: 99 dB(A)

RECOMMENDED ACCESSORIES



Saw Chain PRO 40cm Saw Chain 40 cm (1.1mm)
F016800647



Lubricating Oil 1L Chain Oil
F016800642

TELESCOPIC CORDLESS CHAINSAW - PRUNING SAW GKE 18V-25 TP

Product Number
06008D2000

Included in this model:
• Soabbard 25 cm
• Sorenh
• Shoulder strap



TECHNICAL DATA

Brushless Motor
Telescopic Handle: 2.9 m
Bar length: 25 cm
Chain oil tank capacity: 80 ml
Noise level: 97 dB(A)

RECOMMENDED ACCESSORIES



PRO 25cm Saw Chain (1,1 mm)
F016800661



Lubricating Oil 1L Chain Oil
F016800642

CORDLESS HEDGE CUTTER GHE 18V-60

Product Number
06008C9000



TECHNICAL DATA

Brushless Motor
Blade length: 60 cm
Tooth opening: 23 mm
Cutting speed: 1,500 rpm
Noise level: 91 dB(A)

CORDLESS HEDGE TRIMMER TELESCOPIC GHE 18V-50 TP

Product Number
06008D5000



TECHNICAL DATA

Brushless Motor
Telescopic Handle: 2.5 m
Length (blade): 50 cm
Max. cutting thickness: 20 mm
Max. stroke rate: 3400 /min

CORDLESS GRASS TRIMMER GRT 18V-33

Product Number
06008D0000

Included in this model:
• 1 x shoulder strap
• 1 x spool assembly
• Plant protector



TECHNICAL DATA

Brushless Motor
Line diameter: 2.4 mm
Cutting diameter line: 33 cm
Noise level: 90 dB(A)

CORDLESS BRUSH CUTTER GFR 18V-23

Product Number
06008D1000

Included in this model:
• 1x shoulder strap
• 1 x spool assembly
• Plant protector
• Brush cutter blade set
• Locking pin



TECHNICAL DATA

Brushless Motor
Line diameter: 2.4 mm
Cutting width: 23 cm
Blade thickness: 2 mm

EFFICIENT CLEANING RESULTS WITH BOSCH

Bosch high-pressure washers have been developed with the aim of removing stubborn dirt under tough working conditions.

Bosch Professional



For more information:
www.bosch-professional.com/ae/en/



BOSCH

HIGH-PRESSURE WASHER GHP 5-55

Product Number
0600910470

Included in this model:
- Bosch gun
- Adjustable 3-in-1 lance (stainless steel)



HEAVY
DUTY



TECHNICAL DATA

Rated input power: 2200 W
Max. pressure: 130 bar
Hose length: 8 m
Cable length: 5 m
Noise level: 92 dB(A)

HIGH-PRESSURE WASHER GHP 5-65 X

Product Number
0600910670

Included in this model:
- Bosch gun
- Adjustable 3-in-1 lance (stainless steel)



HEAVY
DUTY



TECHNICAL DATA

Rated input power: 2400 W
Max. pressure: 160 bar
Hose length: 10 m
Cable length: 5 m
Noise level: 92 dB(A)

HIGH-PRESSURE WASHER GHP 5-75 X

Product Number
0600910800

Included in this model:
- Bosch gun
- Adjustable 3-in-1 lance (stainless steel)
- Roto nozzle



HEAVY
DUTY



TECHNICAL DATA

Rated input power: 2600 W
Max. pressure: 185 bar
Hose length: 10 m
Cable length: 5 m
Noise level: 91 dB(A)

HIGH-PRESSURE WASHER GHP 5-13 C

Product Number
0600910070

TECHNICAL DATA

Rated input power: 2300 W
Max. pressure: 140 bar
Hose length: 8 m
Cable length: 5 m
Noise level: 91 dB(A)

HEAVY
DUTY



RECOMMENDED ACCESSORIES



Bosch 360 Gun
F016800536



Rotary Nozzle
F016800536



Compact
High-Pressure Brush
F016800592



Car Cleaning Kit
F016800572



90° Nozzle
F016800581



Home & Car Kit
F016800611



Water Filter
F016800577



Varlo Fan Jet Nozzle
F016800582



360 Cleaning Kit
F016800612



Trio Nozzle
F016800583

HIGH-PRESSURE WASHER

EASY AQUATAK 100

Compact and quick
for effortless cleaning
performance.



Order No.	06008A7EL1
Technical Data	
Motor Power	1,100 W
Max. pressure	100 bar
Max. flow rate	5.5 l/min
Max. flow temperature	40 °C
Hose length	3 m
Weight	3.72 kg

EASY AQUATAK 110

Compact and quick
for effortless cleaning
performance.



Order No.	06008A7FL0
Technical Data	
Motor Power	1,300 W
Max. pressure	110 bar
Max. flow rate	5.5 l/min
Max. flow temperature	40 °C
Hose length	3 m
Weight	4.8 kg

EASY AQUATAK 120

Compact and quick
for effortless cleaning
performance.



Order No.	06008A7971
Technical Data	
Motor Power	1,500 W
Max. pressure	120 bar
Max. flow rate	5.8 l/min
Max. flow temperature	40 °C
Hose length	5 m
Weight	5.10 kg

UNIVERSAL AQUATAK 125

Enjoy fast, flexible, and
effortless cleaning on a wide
variety of jobs.



Order No.	06008A7AL0
Technical Data	
Motor Power	1,500 W
Max. pressure	125 bar
Max. flow rate	6 l/min
Max. flow temperature	40 °C
Hose length	5 m
Weight	6.4 kg

UNIVERSAL AQUATAK 130

Fast, flexible, and effortless
cleaning on a wide variety
of jobs.



Order No.	06008A7BL0
Technical Data	
Motor Power	1,700 W
Max. pressure	130 bar
Max. flow rate	7 l/min
Max. flow temperature	40 °C
Hose length	6 m
Weight	8.42 kg

ADVANCED AQUATAK 140

High-performance cleaning for
the most stubborn dirt.



Order No.	06008A7D70
Technical Data	
Motor Power	2,100 W
Max. pressure	140 bar
Max. flow rate	7.5 l/min
Max. flow temperature	40 °C
Hose length	5 m
Weight	18.65 kg





BOSCH

Invented for life

Aquatak 100/110/120/125/130/135 Accessories Range.



Adapter for Low Pressure Nilfisk Accessories	F016800465		Car Cleaning Kit	F016800572	
Kärcher Adapter	F016800575		Home & Car Kit	F016800611	
Aquatak Adapter	F016800576		360° Kit	F016800612	
High-Pressure Detergent Nozzle (550ml)	F016800415		Bosch 360° Gun	F016800536	
High-Pressure Detergent Nozzle 450ml	F016800509		Rotary Nozzle	F016800580	
Water Filter, Large	F016800440		90° Nozzle	F016800581	
Water Filter	F016800577		Variable Fan Jet Nozzle	F016800582	
High Pressure Hose 6m	F016800360		Trio Nozzle	F016800583	
Extension Hose 6m (135 bar)	F016800361		AquaSurf 280 Patio Cleaner	F016800466	
Drain Cleaner 10m* (130 bar)	F016800362		AquaSurf 250 Patio Cleaner	F016800486	
Drain Cleaner 10m (160 bar)	F016800483		AquaSurf 280 Multi Surface Cleaner	F016800467	
Suction Nozzle	F016800356		Compact Brush	F016800592	
Self Priming Kit	F016800421		Wash Brush	F016800359	

*Only compatible with UniversalAquatak 125/130

SYMBOLS AND THEIR MEANINGS



SDS Plus

Optimum power transmission.
For breakers/drills in the 2-4 kg class.



SDS Max

Optimum power transmission.
For breakers/drills and breakers from the 5 kg class onwards.



Heavy Duty

We offer reliability, first-class service, and a unique lifespan. All Bosch Heavy Duty products are manufactured with a spirit of technology and innovation, ensuring the highest operational uptime.



BITURBO

Its technology and new high-performance brushless motor fully utilize the power of ProCORE18V batteries, overcoming even the most demanding tasks.



Brushless Motor

Longer motor lifespan, extended runtime, and increased power.



Lithium-Ion

Thanks to lithium-ion technology, the batteries have no memory effect and no self-discharge.



Esnek Güç Sistemi

The battery is 100% compatible with all power tools in its voltage class. For the longest runtime, choose XL batteries; for the most comfortable handling, opt for a compact battery.



Cool Pack Technology

Prevents overheating thanks to a special heat-conducting housing. Optimal protection for battery cells.



Battery Charge Level Indicator

Indicates the remaining battery charge level.



Modes

More efficient work thanks to adjustable modes.



Kick Back Control

The machine's automatic stop technology. Reduces the risk of sudden machine reactions.



Vibration Control

Low vibration achieved through rubber mounting parts and foam pads added to the handles.



Vario-Lock Sistemi

Easily adjust the chisel position. Adapts to every working condition.



Forward-Reverse Rotation

For tightening and loosening screws.



Electronic Brake

Ensures that the tool does not stop immediately when turned off.



Electronic Angle Detection

The user can select one of the predefined angles or enter a desired angle via the application.



Rotation Control Clutch

Protection for the user and the machine in case of overload and jamming.



Click & Clean System

3 great advantages:

- Clear visibility of the working surface for fast and efficient operation.
- Harmful dust is immediately absorbed, protecting your health.
- Less dust means a longer lifespan for your power tool and accessories.



Saw Blade Pendulum Motion

3- and 4-stage adjustable saw blade pendulum motion. Ensures optimal curve-cutting capability, high cutting capacity, and blade efficiency.



Variable Speed

Easy and precise control of RPM thanks to variable speed.



Speed Selection

The pre-set speed selection function ensures the best results in applications requiring speed adjustment based on the material.



Torque Selection

Different torque settings provide precise control.



Dust Extraction System

Dust extraction directly into the integrated dust bag on the power tool and/or via a multi-purpose vacuum cleaner.



Automatic Filter Cleaning

While maintaining constant suction power, the automatic filter cleaning system operates every 15 seconds.



Direct Cooling

For resistance to overload and a long service life.



Chiseling

No rotational movement, only impact force.



1/2" External Square Tool Holder



1/4" External Hex Tool Holder



Powersave Feature

When this mode is activated, the motor automatically starts as soon as the screw touches the wall.



Individual Speed Setting



User Interface

Enables direct feedback and machine adjustment.



One Handed Activation

Power switch operated with the thumb for effective one-handed use.



Ignition Mode Switching

The user can choose between single and contact (bump-fire) activation modes.



Electronic Cell Protection

Protects the battery from overheating, overload, and deep discharge.



Soft Start

During initial operation, the motor load and torque are temporarily reduced.



Overload Protection

In overload situations, the power tool shuts itself off, extending its lifespan.



PROtection Switch

The machine shuts off as soon as the safety switch is released.



Soft Grip

For comfortable use



Restart Protection

Prevents the power tool from restarting automatically after a power outage. The tool must be consciously and manually reactivated.



Electronic Motor Protection

In cases of overload, overheating, and/or blockage, the motor automatically shuts off.



Protection Guard

The anti-rotation safety guard prevents splashing even if the disc breaks.



Low Recoil

Thanks to very low kickback, it prevents injury to the user's wrist.



Ergonomic

Ergonomic design, compact handling.



Anti-Roll

Designed to prevent rolling.



Belt Clip/Hook



Toolless

No additional tools are required for configuring the device.



LED Light

Illuminating the work area.



L-BOXX Ready

Easy integration with Bosch transport and storage equipment.



2 Gear

Thanks to the 2-speed planetary gearbox, optimal torque for screwdriving and ideal speed for drilling.



3 YEARS WARRANTY*

1-Year Warranty: Valid for all professional power tools and measuring devices. For more details, see warranty terms and conditions.

<https://www.bosch-professional.com/em/en>



SDS Plus

Optimum power transmission.
For breakers/drills in the 2-4 kg class.



SDS Max

Optimum power transmission.
For breakers/drills and breakers from the 5 kg class onwards.



Heavy Duty

We offer reliability, first-class service, and a unique lifespan. All Bosch Heavy Duty products are manufactured with a spirit of technology and innovation, ensuring the highest operational uptime.



BITURBO

Its technology and new high-performance brushless motor fully utilize the power of ProCORE18V batteries, overcoming even the most demanding tasks.



Brushless Motor

Longer motor lifespan, extended runtime, and increased power.



Lithium-Ion

Thanks to lithium-ion technology, the batteries have no memory effect and no self-discharge.



Esnek Güç Sistemi

The battery is 100% compatible with all power tools in its voltage class. For the longest runtime, choose XL batteries; for the most comfortable handling, opt for a compact battery.



Cool Pack Technology

Prevents overheating thanks to a special heat-conducting housing. Optimal protection for battery cells.



Battery Charge Level Indicator

Indicates the remaining battery charge level.



Modes

More efficient work thanks to adjustable modes.



Kick Back Control

The machine's automatic stop technology. Reduces the risk of sudden machine reactions.



Vibration Control

Low vibration achieved through rubber mounting parts and foam pads added to the handles.



Vario-Lock Sistemi

Easily adjust the chisel position. Adapts to every working condition.



Forward-Reverse Rotation

For tightening and loosening screws.



Electronic Brake

Ensures that the tool does not stop immediately when turned off.



Electronic Angle Detection

The user can select one of the predefined angles or enter a desired angle via the application.



Rotation Control Clutch

Protection for the user and the machine in case of overload and jamming.



Click & Clean System

3 great advantages:

- Clear visibility of the working surface for fast and efficient operation.
- Harmful dust is immediately absorbed, protecting your health.
- Less dust means a longer lifespan for your power tool and accessories.



Saw Blade Pendulum Motion

3- and 4-stage adjustable saw blade pendulum motion. Ensures optimal curve-cutting capability, high cutting capacity, and blade efficiency.



Variable Speed

Easy and precise control of RPM thanks to variable speed.



Speed Selection

The pre-set speed selection function ensures the best results in applications requiring speed adjustment based on the material.



Torque Selection

Different torque settings provide precise control.



Dust Extraction System

Dust extraction directly into the integrated dust bag on the power tool and/or via a multi-purpose vacuum cleaner.



Automatic Filter Cleaning

While maintaining constant suction power, the automatic filter cleaning system operates every 15 seconds.



Direct Cooling

For resistance to overload and a long service life.



Chiseling

No rotational movement, only impact force.



1/2" External Square Tool Holder



1/4" External Hex Tool Holder



Powersave Feature

When this mode is activated, the motor automatically starts as soon as the screw touches the wall.



Individual Speed Setting



User Interface

Enables direct feedback and machine adjustment.



One Handed Activation

Power switch operated with the thumb for effective one-handed use.



Ignition Mode Switching

The user can choose between single and contact (bump-fire) activation modes.



Electronic Cell Protection

Protects the battery from overheating, overload, and deep discharge.



Soft Start

During initial operation, the motor load and torque are temporarily reduced.



Overload Protection

In overload situations, the power tool shuts itself off, extending its lifespan.



PROtection Switch

The machine shuts off as soon as the safety switch is released.



Soft Grip

For comfortable use



Restart Protection

Prevents the power tool from restarting automatically after a power outage. The tool must be consciously and manually reactivated.



Electronic Motor Protection

In cases of overload, overheating, and/or blockage, the motor automatically shuts off.



Protection Guard

The anti-rotation safety guard prevents splashing even if the disc breaks.



Low Recoil

Thanks to very low kickback, it prevents injury to the user's wrist.



Ergonomic

Ergonomic design, compact handling.



Anti-Roll

Designed to prevent rolling.



Belt Clip/Hook



Toolless

No additional tools are required for configuring the device.



LED Light

Illuminating the work area.



L-BOXX Ready

Easy integration with Bosch transport and storage equipment.



2 Gear

Thanks to the 2-speed planetary gearbox, optimal torque for screwdriving and ideal speed for drilling.



1-Year Warranty: Valid for all professional power tools and measuring devices. For more details, see warranty terms and conditions.

<https://www.bosch-professional.com/am/en>



User calibration enables fast and easy calibration for precise operation.



Green Laser Technology
For a more visible laserline.



IP 54 Protection
Protection against dust and splashing water.



IP 65 Protection
Protection against dust and splashing water.



IP 67 Protection
Protection against dust and splashing water.



Click System
Thanks to the patented Click system, multiple BOXX units can be stacked securely and transported easily. (Bosch Transport Systems)



Durable
BOXX units are resistant to 100 kg of weight and can carry up to 25 kg.



Theft Protection
Thanks to the optional locking function.



Metal Gear
Thanks to the full metal gear construction, it ensures optimal power transmission and reduced wear.



Shock Warning
An alarm warning function that activates when the tool is moved.



Detection of voltage-carrying wires



Metal Detection



Wood Detection



Detection of water-filled plastic pipes



Laser Class 2
Laser class in measuring devices.



Laser Class 3
Laser class in measuring devices.



Dual Power Source
12V battery and charger dual power source.



4x Batteries
Power source: 4x AA batteries.



Operation with receiver
Operation with a receiver to provide a greater working range.



Easy Positioning
Easy line positioning around the plumb point.



Mounting Accessory
Precisely adjustable integrated rotary mounting accessory.



Slide Mechanism



LB 10
LB 10 holder with strong magnets.



Working Range
Up to 50 meters.



High Durability
Drop-resistant from a height of 2m with tripod.



Dual Slope
Dual slope allows the creation of inclined surfaces on two axes.



3x360° Laser Line



Easy to Use



Transport Lock
Pendulum transport lock activated when the tool is turned off.



Voice Note
Integrated microphone and speaker for taking voice notes.



Dual Camera



Up Indicator
Thanks to the function, you can always see the upward direction.



Visual Camera



Connectivity
via Bluetooth

BOSCH POWER TOOLS - PRODUCT WARRANTY

'Central Motors and Equipment LLC' warrants that all BOSCH power tools purchased through 'Central Motors Equipment LLC' or any of its authorized/ registered dealers, shall be covered under warranty, against manufacturing defects, if any, for one year (12 months) from the date of purchase, upon presenting copy of proof of purchase.

To the extent permitted by law, any warranty or condition implied by law, warranty obligation shall be limited to the repair or replacement of parts, without charge.

Warranty shall be nullified, void and non-applicable in case of:

- Any misuse, overload or fault from the user /customer.
- Any repair attempted by any Service Station other than 'Central Motors & Equipment LLC'.
- Any non-genuine part(s) found in the tool
- Normal wear & tear components (e.g., Carbon brushes/ O-rings etc.) and consumables like grease etc.

The relevant power tool must be deposited at, 'Central Motors & Equipment LLC' or to one of its authorized 'Collection Point' accompanied by an copy of original invoice.

If any artificial invoice submitted for warranty claim than customer account will be blocked for any future dealing without prejudice to any legal rights the Company may have.

THIS LIMITED WARRANTY DOES NOT APPLY TO CONSUMABLES, SUCH AS CARBON BRUSHES AND ACCESSORY ITEMS SUCH AS CIRCULAR SAW BLADES, DRILL BITS, ROUTER BITS, JIGSAW BLADES, SANDING BELTS, GRINDING WHEELS AND OTHER RELATED ITEMS

Terms and Conditions:

- Warranty is valid for only 1 year period starting from the date of purchase.
- Customer must present purchase invoice copy generated by CM&E or its authorized dealers, for Warranty claim.
- Wear and Tear repairs are subject to cost.
- Accessories will not be covered under warranty.
- Warranty only subjects to manufacturing defects.
- No claim for warranty would be preceded if there is a sign of misuse, overload or fault from the customer (Use of non-genuine SKU's) in usage.
- No claim for warranty would be processed if tool is received in open condition.
- Customer account will be blocked if any artificial invoice being submitted by customer to claim warranty.

Service Center Contacts:

Dubai: 04 3090920 | Abu Dhabi: 02 4017745 | Sharjah: 06 5932753
powertoolsaftersales@centralmotors.ae



SERVICE



**AFFORDABLE
PRICES &
PROFESSIONAL
SERVICES**



FIND THE CLOSEST SERVICE CENTER TO YOU

Use QR Codes to find out each Branches Location!

CENTRAL MOTORS & EQUIPMENT

Web Page: www.cmeuae.ae Email: powertoolsaftersales@centralmotors.ae



المركبة للسيارات والمعدات
CENTRAL MOTORS & EQUIPMENT
MEMBER OF ALFAHIM GROUP

Exclusive Distributor of BOSCH Power Tools in the UAE

BRANCH



Address: 37/1, 16 Street, M15,
Mussafah, P.O Box 71343,
Abu Dhabi, United Arab Emirates
Phone: 0097124017745

BRANCH



Address: Al Quoz
Industrial Area 4,
P.O Box 26255,
Dubai, United Arab Emirates
Phone: 0097143090930
0097143090920

BRANCH



Address: Maleha Street,
Showroom 23-24,
P.O Box 1984,
Sharjah, United Arab Emirates
Phone: 0097165932777



Visit our website:

www.bosch-professional.com/middle-east/en/



For detailed
information
please scan
the QR code



Visit our Facebook page:

www.facebook.com/BoschPTME



For detailed
information
please scan
the QR code



Visit our Youtube channel:

www.youtube.com/@BoschprofessionalMI-AR/featured



For detailed
information
please scan
the QR code



BOSCH