


Product code: 2102

DUTARP Tarpaulins can be stitched and welded by high frequency welding machine with special Grommets/ Eyelets, Reinforcements and Webbing as per customer's requirements maximum size up to 60FT x 60FT (18mtr x 18mtr)

| PVC-2102 | |
|---|--|
| Characteristics | Applications |
| <ul style="list-style-type: none"> • Excellent Water Proof • U.V Treated • Anti Cold Crack • Oil Resistance • Fire Retardent | <ul style="list-style-type: none"> • Tents • Tarpaulins • Oil & Gas Stores • Equipment Covers • Boat Covers |
| Product Code | 2102 |
| Finished Coated Weight | 300 gsm/SQM |
| Base Fabric | Polyester 200Dx500D, 18x12/Inch |
| Tensile Strength | L 1600N/5cm W1475N/5cm (ASTM D5035) |
| Tear Resistance | L300N/5cm W279/5cm (ASTM D1004) |
| Adhesion | L ≥ 80N W ≤ 80N (ASTM D5035) |
| Thickness | 0.35mm |
| Width | 72 Inch (180 cms) |
| Fire Retardancy | Passed (BS5867) |
| Temperature Resistance | -20 ~ 70°C |
| Package | 72" x 50 yds |



Standard Colours



| Also available in ready made sizes: | | |
|-------------------------------------|---------------------------|---------------------------|
| 18 FT x 24 FT (5.5m x 7.2m) | 30 FT x 30FT (9m x 9m) | 60 FT x 60 FT (18m x 18m) |
| 20 FT x 20 FT (6m x 6m) | 40 FT x 40 FT (12m x 12m) | |

FIRE RETARDANT CANVAS

Product code: FRC - 22



| Product Code | | FRC-22 | |
|--------------|------|--|---------------|
| Description | | Fire Retardant Cotton Canvas | |
| Weave | | Plain 1/1 | |
| Yarn | Warp | 10/2 | 10/2 |
| Tex | Weft | 10/2 | 10/2 |
| Width | | 180 cm | 72 Inch |
| Thickness | | 0.45 mm | 0.018 Inch |
| Weight | | 450 G/SQM | 16 OZ/SQ Yard |
| Thread | Warp | 18 Per Cm | 46 Per Inch |
| Count | Weft | 9 per Cm | 24 per Inch |
| Tensile | Warp | 6000 N/5 Cm | 666 Lbs/Inch |
| Strength | Weft | 4500 N/5 Cm | 500 Lbs/Inch |
| Treatment | | The Fabric is Fire Retardant and has been tested as per BS7175:1989 - Ignition sources 0 & 1 | |
| Application | | This material is suitable for Protection against metal grinding and light welding spark | |

